


HR-LED351

3" LEDme® Open Reflector Downlight Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Square recessed trim with interior open reflector.
For use with HR-LED309 series housings.

FEATURES

- Less than 1/8" thick, super low profile die-cast aluminum trim
- Recessed depth from LEDs to trim edge is 2 3/8"
- Narrow flood beam spread
- 100,000 hour rated life
- Deep regression produces a very low glare with 40° cut-off angle
- Handles surfaces up to 3/4" thick
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction.
Three heavy gauge retention clips hold trim firmly to housing.

Light Source: Utilizes three 3W LED's (included with housing).
See individual housing for wattage rating.

Finish: Powder coat paint or plated metal finish.
Available in Black baffle w/Brushed Nickel trim (BK/BN)
and White baffle w/White trim (WT/WT).

Standards: UL & CUL Listed.

ORDER NUMBER

| Model # | Finish | Reflector/Trim |
|------------------|------------------------------|---|
| HR-LED351 | BK/BN WT/WT | <i>Black/Brushed Nickel</i> <i>White/White</i> |

FINISHES


BK/BN



WT/WT



PHOTOMETRY



Beam Angle: 32°

HR-LED351

-

Example: **HR-LED351-WT/WT**

COMPATIBLE HOUSINGS (ORDER SEPARATELY)

| Rating | Model # | Installation | Color Temp | Watt | Lumens | CRI | Input | Current | Dimensions | Cutout | | | |
|----------|---------------|------------------|------------|-------|--------|-----|--------------|---------|--------------------------|--------|----|-----------------------|-----|
| IC-Rated | HR-LED309-NIC | New Conctruction | 27 | 2700K | 5.8W | 295 | 120V 50/60Hz | 450mA | L: 15-24½" W: 6¾" H: 5⅝" | 3⅞" | | | |
| | | | W | 3000K | | 295 | | | | | 85 | | |
| | HR-LED309-RIC | Remodel | 35 | 3500K | | 314 | | | | | 80 | L: 11¼" W: 3¾" H: 5⅝" | 3⅞" |
| | | | C | 4500K | | 375 | | | | | | | |
| Non-IC | HR-LED309-N | New Conctruction | 27 | 2700K | 8W | 413 | 120V 50/60Hz | 700mA | L: 15-24½" W: 6¾" H: 5⅝" | 3⅞" | | | |
| | | | W | 3000K | | 413 | | | | | 85 | | |
| | HR-LED309-R | Remodel | 35 | 3500K | | 440 | | | | | 80 | L: 11¼" W: 3¾" H: 5⅝" | 3⅞" |
| | | | C | 4500K | | 515 | | | | | 75 | | |

Example: **HR-LED309-NIC-27**

See individual housing spec sheets for complete information.

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585