


HR-LED418-RIC

4" LEDme® – IC-Rated, Remodel Housing

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

4 inch LEDme® IC-Rated remodel housing, includes six 3W LED's.
For use with LEDme® 4 inch trims.

FEATURES

- Energy Star®
- Cutout: 4 3/8"
- 100,000 hour rated life
- Accommodates ceiling thickness up to 1"
- UL and CUL Listed
- 5 year WAC Lighting product warranty

FIXTURE PERFORMANCE

Model #	Color Temp	Watt	Lumens	Efficacy	CRI
HR-LED418-RIC-27	2700K	10.2W	639	58.1 Lm/W	85
HR-LED418-RIC-30	3000K	10.2W	639	58.1 Lm/W	85
HR-LED418-RIC-35	3500K	10.2W	681	62.0 Lm/W	80
HR-LED418-RIC-40	4000K	10.2W	815	70.0 Lm/W	75

ORDER NUMBER

Model #	Color Temp
HR-LED418-RIC	27 2700K
	30 3000K
	35 3500K
	40 4000K

HR-LED418-RIC



Example: HR-LED418-RIC-C

SPECIFICATIONS

Construction: Die-cast aluminum heat sink painted black.
Housing and junction box are 20 gauge steel.

J-Box: Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: Electronic driver, 120VAC/60Hz input, 10.2W output, 450mA current. Power factor >0.9. Dimming with thermal protection.

Light Source: Includes six 3W ANSI compliant Warm/Neutral LEDs for the finest color consistency possible. Replacement modules available.

Dimming: May be dimmed to 1% with electronic low voltage (ELV) dimmer.

Mounting: Three heavy gauge inner retention clips push out onto ceiling or other mounting surface to firmly hold housing in place. Accommodates surface up to 1/2" thick. 4 3/8" cutout hole.

Rating: IC-Rated: Suitable for direct contact with insulation.

Standards: UL & CUL Listed.

REPLACEMENT MODULES

Model #	Color Temp
RM-6X3-27	2700K
RM-6X3-30	3000K
RM-6X3-35	3500K
RM-6X3-40	4000K

COMPATIBLE TRIMS

Model #	Description	Finish – (where there is a slash (/) the letters correspond as: interior finish/exterior finish)
HR-LED411	Round, Open Reflector Downlight	Black/Brushed Nickel (BK/BN), Black/White (BK/WT), White/White (WT/WT)
HR-LED421	Round, Step Baffle Downlight	White/White (WT/WT)
HR-LED431	Round, Shower light	Chrome (CH), White (WT)
HR-LED451	Square, Open Reflector Downlight	Black/Brushed Nickel (BK/BN), Black/White (BK/WT), White/White (WT/WT)
HR-LED471	Square, Shower light	Chrome (CH), White (WT)

Example: HR-LED411-BK/BN

See individual trim spec sheets for complete information.

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585


HR-LED418-RIC

Photometrics


WAC LIGHTING

Responsible Lighting®


2700K




3000K



3500K



4500K



WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050


Western Distribution Center
1750 Archibald Avenue • Ontario, CA 91760
Phone (800) 526.2588 • Fax (800) 526.2585

HR-LED418-R

4" LEDme® – Non-IC, Remodel Housing

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

4 inch LEDme® Non-IC remodel housing, includes six 3W LED's.
For use with LEDme® 4 inch trims.

FEATURES

- Energy Star®
- Cutout: 4 3/8"
- 100,000 hour rated life
- Accommodates ceiling thickness up to 1"
- UL and CUL Listed
- 5 year WAC Lighting product warranty

FIXTURE PERFORMANCE

Model #	Color Temp	Watt	Lumens	Efficacy	CRI
HR-LED418-R-27	2700K	16W	846	56.4 Lm/W	85
HR-LED418-R-30	3000K	16W	846	56.4 Lm/W	85
HR-LED418-R-35	3500K	16W	901	60.1 Lm/W	80
HR-LED418-R-40	4000K	16W	1135	67.1 Lm/W	75

ORDER NUMBER

Model #	Color Temp
HR-LED418-R	27 2700K
	30 3000K
	35 3500K
	40 4000K

HR-LED418-R



Example: HR-LED418-R-C

SPECIFICATIONS

Construction: Die-cast aluminum heat sink painted black.
Housing and junction box are 20 gauge steel.

J-Box: Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: Electronic driver, 120VAC/60Hz input, 16W output, 700mA current.
Power factor >0.9. Dimming with thermal protection.

Light Source: Includes six 3W ANSI compliant Warm/Neutral LEDs for the finest color consistency possible. Replacement modules available.

Dimming: May be dimmed to 1% with electronic low voltage (ELV) dimmer.

Mounting: Three heavy gauge inner retention clips push out onto ceiling or other mounting surface to firmly hold housing in place.
Accommodates surface up to 1/2" thick. 4 3/8" cutout hole.

Rating: Non-IC: insulation must be kept at least 3" away from the housing.

Standards: UL & CUL Listed.

REPLACEMENT MODULES

Model #	Color Temp
RM-6X3-27	2700K
RM-6X3-30	3000K
RM-6X3-35	3500K
RM-6X3-40	4000K

COMPATIBLE TRIMS

Model #	Description	Finish – (where there is a slash (/) the letters correspond as: interior finish/exterior finish)
HR-LED411	Round, Open Reflector Downlight	Black/Brushed Nickel (BK/BN), Black/White (BK/WT), White/White (WT/WT)
HR-LED421	Round, Step Baffle Downlight	White/White (WT/WT)
HR-LED431	Round, Shower light	Chrome (CH), White (WT)
HR-LED451	Square, Open Reflector Downlight	Black/Brushed Nickel (BK/BN), Black/White (BK/WT), White/White (WT/WT)
HR-LED471	Square, Shower light	Chrome (CH), White (WT)

Example: HR-LED411-BK/BN

See individual trim spec sheets for complete information.

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585


HR-LED418-R

Photometrics


WAC LIGHTING

Responsible Lighting®


2700K




3000K



3500K



4500K



WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center
1750 Archibald Avenue • Ontario, CA 91760
Phone (800) 526.2588 • Fax (800) 526.2585