

## Catalog No. TGN3326



**Description 600A 3P GD N1 240V NONFUSE**

**UPC No 783164008869**

**Products > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > General Duty**

- Designed for residential and light commercial applications where duty is not severe.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.
- Meets or exceeds NEMA KS1 standard for enclosed switches - type GD.
- Fusible and non-fusible switches available (consult BuyLog for interrupt ratings).
- Quick-make, quick-break mechanism (30-200 amp).
- 60/75°C conductor rating.

### Specifications

#### Descriptors

Category	General Duty
----------	--------------

#### Specifications

Amperage	600 A
Poles	3
Wires	3
Fusing	No Fuse
Enclosure	NEMA 1 (Indoor)
Wire Range (Cu/Al)	(2) 4-500
240 Vac, NEC Std, 3-ph	100
GSA Compliance	Yes

#### Classifications

CSA Certified	Yes
---------------	-----

#### Dimensions

Height	49.9
Depth	9
Width	22.9
Weight	120

### Publications

Title	Publication No.	Publication Type
<a href="#">600A - Safety Switches</a>		
1 page outline drawing in .pdf format.	10103091-SH116	Drawings-Outline and Dimensional
<a href="#">General Duty Safety Switches: 30-600 Amp, 240 Vac</a>		
1 page. For residential and light commercial applications.	DEE-576	Brochures

**Additional Documentation:** Visit our [Publication Library](#) to find technical documentation, time current curves, CSI Specifications and promotional literature.