



# KT-LED45HID-E26-850-D

HID REPLACEMENT LED LAMP

## **DESCRIPTION**

45W HID Replacement LED Lamp | 5000K | >83 CRI | IP64 Rated





C(UL)US LISTED

RoHS Compliant

## **PRODUCT FEATURES**

- Replacement for Conventional Metal Halide Lamp
- Non-Dimmable; Do Not Dim
- 50,000+ Hour Lifetime
- Environmentally Friendly: No Mercury Used
- Instant Startup
- UL Listed

- Operating Temperature: -29°C/-20°F to 60°C/140°F
- Integral Driver, Eliminates the Need for External Driver or Ballast; Includes 4kV Surge Protection
- IP64 Rated; Integrated Heat Sink Quickly Dissipates Heat and Guides Water Intrusion Out of the Lamp

## **OPERATING SPECIFICATIONS**

## **ELECTRICAL CHARACTERISTICS**

| Input Voltage | Power Consumption | Power Factor | Input Current                |
|---------------|-------------------|--------------|------------------------------|
| 120-277Vac    | 45W               | >0.9         | 0.42A @ 120V<br>0.18A @ 277V |


## **RATED LIFE**

| L70 (Hours) | 50,000 |
|-------------|--------|


## PHOTOMETRIC CHARACTERISTICS

| Color Temperature (CCT)     | 5000K    |  |
|-----------------------------|----------|--|
| Luminous Flux               | 6350 lm  |  |
| Color Rendering Index (CRI) | >83      |  |
| Efficacy                    | 141 lm/W |  |
| Visible Light Area          | 360°     |  |

### SPECTRAL DISTRIBUTION



### **LUX DISTANCE CURVE**



Keystone Technologies • 1390 Welsh Road, North Wales, PA 19454 • Phone (800) 464-2680 • Fax (888) 966-0556 • www.keystonelamp.com





# KT-LED45HID-E26-850-D

HID REPLACEMENT LED LAMP

## WIRING DIAGRAM

### STEP 1


**Disconnect power.** Disconnect and remove existing ballast, capacitor, and/or ignitor (where applicable) from fixture.


#### STFP 2


Rewire for line voltage to the lamp socket.


### STEP 3

Install new LED replacement lamp. Ensure lamp is operating properly when power is turned on.











## PHYSICAL CHARACTERISTICS





## LAMP DIMENSIONS

| A (Illuminated Length) | 5.83"  |  |
|------------------------|--------|--|
| B (Body Length)        | 10.16" |  |
| C (Diameter)           | 3.43"  |  |

BASE TYPE: E26 (Medium)

## **ORDERING INFORMATION**

| ORDER CODE               | PACKAGING STYLE                       | PACK QTY. | ITEM STATUS |
|--------------------------|---------------------------------------|-----------|-------------|
| KT-LED45HID-E26-850-D-DP | Distributor Pack (Individual Cartons) | 16        | Quick Ship  |

## CATALOG NUMBER BREAKDOWN

