

## KTLD-2LT5HE-UV-8C-VDIM /G2

### CONSTANT CURRENT LED DRIVER FOR TYPE C T5HE LAMPS

#### DESCRIPTION

Constant Current Output | 120–277V Input | 0–10V Dimming



RoHS  
Compliant



**7YEAR**  
WARRANTY

**DRIVER TYPE:** Constant Current

**OUTPUT CURRENT:** 0.185A × 2 Channels

**INPUT POWER:** 18W

**MAX. CURRENT** 0.17A@120V, 0.10A@277V

**MAX. OUTPUT POWER:** 16W

**WARRANTY:** 7 Years



#### PRODUCT FEATURES


- Compatible with Keystone external drive T5HE LED lamps
- Meets FCC Part 15 (Class B) consumer limits
- Short circuit overload and open load protection
- Type 1 outdoor, suitable for dry and damp locations
- UL8750 Recognized component
- Dimmable with 0–10V Dimmer, dim minimum 10%
- Operating temperature: –20°C/–4°F to 45°C/113°F
- 85°C/185°F maximum case temperature
- Input frequency: 50/60 Hz
- THD: < 20%
- 70,000 hour lifetime

#### ELECTRICAL SPECIFICATIONS

INPUT CHARACTERISTICS				OUTPUT CHARACTERISTICS			FEATURES
Input Voltage	Input Power	Power Factor	Max. Current	Max. Output Power	Max. Current	Output Voltage	Efficiency
120–277Vac	18W	>0.9	0.17A@120V 0.10A@277V	16W	0.185A × 2 Channels	36–45Vdc	89%

#### MECHANICAL SPECIFICATIONS

##### CASE DIMENSIONS



LENGTH (L)	9.53"
WIDTH (W)	1.32"
HEIGHT (H)	1.10"


\*TC Point (85°C) is noted on each driver label

## KTLD-2LT5HE-UV-8C-VDIM /G2

CONSTANT CURRENT LED DRIVER FOR TYPE C T5HE LAMPS


### WIRING

#### DOUBLE-ENDED WIRING



\* For 1 lamp application, cap off 1 blue lead

#### SINGLE-ENDED WIRING



\* For 1 lamp application, cap off 1 blue lead

#### STANDARD LEAD LENGTHS\*

Input	Black	30.00"
	White	30.00"
Output	Red	30.00"
	Blue	30.00"
Dimming	Purple	30.00"
	Pink	30.00"

Lead wires are 18 AWG 105° C/600V.

\*Consult Keystone for special lead length requirements.

### ORDERING INFORMATION

Order Code	Pack Quantity	UPC	Easy Code
KTLD-2LT5HE-UV-8C-VDIM /G2	25	843654141305	GYI-59

### CATALOG NUMBER BREAKDOWN

## KTLD-2LT5HE-UV-8C-VDIM /G2

1 2 3 4 5 6 7 8

- 1 Keystone Technologies LED Driver
- 2 Number of Lamps
- 3 Lamp Type
- 4 High Efficiency
- 5 120–277V Input
- 6 Lamp Wattage
- 7 0–10V Dimming
- 8 Generation 2