

Introducing TCP's latest offering of Allusion LED Line—the "incandescent-like" LEDs that offer a unique dimming profile, replicating true incandescent/halogen dimming.

Reasons to choose the Allusion LED Lamps from TCP

- Instant energy savings up to 85% more efficient than incandescent/halogen replacements
- Long life of 25,000/30,000 (SL16)/50,000 (LED Troffer)
 hours minimizes replacement and maintenance costs
- Smooth warm dimming creates the perfect atmosphere
- UL approved for damp locations* can be used outdoors when protected from elements. Can withstand humidity indoors/outdoors
- Shatter resistance lowers the risk of injury and breakage

Ideal Applications

- Table Lamps
- Floor Lamps
- Sconces

- Ceiling Fixtures
- Chandeliers
- Decorative

- Track Lights
- Recessed Downlights
- Grid Ceilings

Specifications:

Voltage	120VAC/ 12 VAC (MR16)
Input Line Frequency	50/60HZ
Lamp Life (Rated)	25,000/30,000 (SL16)/
	50,000 (DTF) hours
Minimum Starting Temp	22°F/-30°C

Maximum Operating Temp	45°C
CRI	80
Color Temperatures	3000K to 2000K/
	3000K to 1800K (MR16)







Allusion LED Lamps

Specifications:



PAR38 40°/25° Beam Angles



PAR30 40°/25° Beam Angles



PAR20 40°/25° Beam Angles



MR16 GU5.3 20° Beam Angle



SL16 Starlight 110° Beam Angle




LED Troffer 120° Beam Angle

ITEM #	DESCRIPTION	VOLTAGE	LED WATTS	WATTAGE EQUIVALENT	LUMENS	LPW	ССТ	COLOR TEMPERATURE	BEAM ANGLE	MOL (inches)	DIA (inches)	BASE
LED PAR38 9	90W Equivalent											
L15P38DNFLA	LED 15W PAR38 30K Allusion NFL	120V	12.5	90	975	78.00	>80	3000K to 2000K	25°	5.4	4.75	E26
L15P38DFLA	LED 15W PAR38 30K Allusion FL	120V	12.5	90	975	78.00	>80	3000K to 2000K	40°	5.4	4.75	E26
LED PAR30	90W Equivalent											
L15P30DNFLA	LED 15W PAR30 30K Allusion NFL	120V	12.5	90	950	76.00	>80	3000K to 2000K	25°	4.7	3.8	E26
L15P30DFLA	LED 15W PAR30 30K Allusion FL	120V	12.5	90	950	76.00	>80	3000K to 2000K	40°	4.7	3.8	E26
LED PAR20	50W Equivalent											
L7P20DNFLA	LED 7W PAR20 30K Allusion NFL	120V	6.5	50	525	80.77	>80	3000K to 2000K	25°	3.4	2.5	E26
L7P20DFLA	LED 7W PAR20 30K Allusion FL	120V	6.5	50	525	80.77	>80	3000K to 2000K	40°	3.4	2.5	E26
LED MR16 5	50W Equivalent											
L712VMR16DNFLA	LED 7W MR16 30K Allusion NFL	12V	6	35	350	58.33	>80	3000K to 1800K	20°	1.9	2.0	5.3
LED SL16 St	arlight											
L15SL16D30A	LED 13W SL16 30K Allusion	120V	13	-	1200	92.30	>80	3000K to 2000K	110°	3.8	6.3	E26
ITEM #	DESCRIPTION	VOLTAGE	LED WATTS	WATTAGE EQUIVALENT	LUMENS	LPW	ССТ	COLOR TEMPERATURE	BEAM ANGLE	LENGTH (inches)	WIDTH (inches)	BASE
LED Troffer 2	2X2											
DTF2UZD3835A	LED 2x2 DTF Wattage Selectable 35K Allusion	120V-277V	38W/29W/23W	-	4200	>110	>80	3500K	120°	24	24	-
DTF2UZD3841A	LED 2x2 DTF Wattage Selectable 41K Allusion	120V-277V	38W/29W/23W	_	4200	>110	>80	4100K	120°	24	24	_
DTF2UZD3850A	LED 2x2 DTF Wattage Selectable 50K Allusion	120V-277V	38W/29W/23W	-	4200	>110	>80	5000K	120°	24	24	_
LED Troffer 2	2X4											
DTF4UZD4635A	LED 2x4 DTF Wattage Selectable 35K Allusion	120V-277V	46W/39W/29W	-	5100	>110	>80	3500K	120°	48	24	-
DTF4UZD4641A	LED 2x4 DTF Wattage Selectable 41K Allusion	120V-277V	46W/39W/29W	_	5100	>110	>80	4100K	120°	48	24	_
DTF4UZD4650A	LED 2x4 DTF Wattage Selectable 50K Allusion	120V-277V	46W/39W/29W	_	5100	>110	>80	5000K	120°	48	24	_

For the most up-to-date specs, please visit www.tcpi.com

TCP[®]









3 YEAR
WARRANTY
*Bulb warranty based on
12 hours use per day

5 YEAR
WARRANTY
*Troffer warranty is
5yrs/50,000hrs

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:	Catalog Number:
Date:	Туре:
Model:	Notes:
Project:	MTCD.
Rep:	TCP we know light.™