

LB125

Branch Circuit Breaker, Standard 1-Pole 25A 120V, 10KA Interrupt Rating



UPC Code: 078477814499

Country Of Origin: Mexico

Leviton Circuit Breakers provide overload and short-circuit protection and feature an all plug-on design. All hot and neutral wires terminate at custom lugs in the panel, not at the circuit breaker*, so the entire panel can be wired at rough-in without circuit breakers installed. Branch circuit breakers are easily plugged-on at final installation. Circuit breakers also feature color indicators in the handle to easily see operational status at-a-glance.

**For applications up to 60A when using copper wire; or 50A when using aluminum wire*

Technical Information

Product Features

Dimensions: 3.9" H x 1.0" W x 3.1" D

Operating Temperature: -40°C to 85°C

Warranty: 10-Year Limited

Weight: 0.42 lbs.

Wiring: All Plug-on

Electrical Specifications

Amperage: 25 A

Pole: 1

Short Circuit Current Rating: 10 KA

Type: Basic

Voltage: 120 VAC

Standards & Certifications

CSA-C22.2 No. 5-02: Yes

EMC Compatibility: Yes

FCC: Yes

RoHS: Yes

UL 489: Yes

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):

+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts/

