



Country Of Origin: China

LB215-S

15A Smart Standard 2-Pole Branch Circuit Breaker

Smart Branch Circuit Breaker, Standard 2-Pole 15A 120/240V, 10KA Interrupt Rating

- SMART Wi-Fi® or Ethernet connection options for remote monitoring and tripping capabilities, remote firmware updates and more
- INTUITIVE My Leviton offers single app control of the control of the Leviton Smart Load Center and the Decora Smart™ Wi-Fi® product lines
- EASY Allows for all wiring at rough-in, without any circuit breakers present

Technical Information

Product Features Short Circuit Current Rating: 10 KA

Dimensions: 3.9" H x 2.0" W x 3.1" D **Type:** Standard **Operating Temperature:** -40°C to 85°C **Voltage:** 120/240 VAC

Smart: YesStandards & CertificationsWarranty: 10-Year LimitedCSA-C22.2 No. 5-02: YesWeight: 0.85 lbs.EMC Compatibility: Yes

Wiring: All Plug-on FCC: Yes
Electrical Specifications RoHS: Yes
Amperage: 15 A UL 489: Yes

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Pole: 2

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

