



UPC Code: 078477814673
Country Of Origin: Mexico

LB230-GF

30A GFCI 2-Pole Branch Circuit Breaker

Branch Circuit Breaker GFCI 2-Pole 30A 120/240V. 10KA Interrupt Rating

Leviton Circuit Breakers provide overload and short-circuit protection and feature an all plug-on design. GFCI circuit breakers offer advanced technology to help protect against electrical shock due to ground faults. All hot and neutral wires terminate at custom lugs in the panel, not at the circuit breaker*, so the entire panel can be wired at rough-in without circuit breakers installed. Branch circuit breakers are easily plugged-on at final installation. Circuit breakers also feature color indicators in the handle to easily see operational status at-a-glance.

*For applications up to 60A when using copper wire; or 50A when using aluminum wire

Technical Information

Product Features Type: GFCI

Operating Temperature: -40°C to 85°C Voltage: 120/240 VAC

Smart: No

Warranty: 10-Year Limited

Electrical Specifications

Standards & Certifications

CSA-C22.2 No. 5-02: Yes

EMC Compatibility: Yes

Amperage: 30 A FCC: Yes
Pole: 2 RoHS: Yes

Short Circuit Current Rating: 10 KA UL 489: Molded Case Circuit Breakers

SPECIFICATION SUBMITTAL

	JOB NAME:	CATALOG NUMBERS:
I		
I	JOB NUMBER:	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

