

# InvisiLED® Pro 2

## 24V LED Tape Light

# WAC LIGHTING

Responsible Lighting®



Tape Section



5 LED "L" Connector

Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

Professional grade white tape light that delivers optimal color consistency and brightness. An ideal system for task or accent lighting applications.

### FEATURES


- Ultra thin profile at 1/8"
- Diodes spaced evenly at 1" on center
- Minimum run length of 1'
- May be field cut every 6" at the end of a run
- 80,000 hour rated life
- 5 year WAC Lighting product warranty

### SPECIFICATIONS

- Construction:** Flexible, silicone cased tape light. Peel and stick 3M construction adhesive on back. Indicating marks on back for field cutting.
- Power Supply:** Remote and plug-in electronic Class 2 transformers  
120VAC 50/60Hz input, 24V 60W and 96W output
- Light Source:** 12 LEDs per foot
- Dimming:** May be dimmed with electronic low voltage (ELV) dimmer.
- Operating Temp:** -4°F – 122°F (-20°C – 50°C) at relative humidity 95%
- Standards:** CEC Title 24 (See below for list of models)  
UL & CUL Listed for damp locations.

### ORDER NUMBER – TAPE SECTION

Model	Watts/ft	Color Temp	CRI	Lumens/ft	Title 24	Length	Qty	Tape Color
LED-TX24	4W/ft	22 2200K	90	275	No	6IN 6 inches	1	WT White
		27 2700K	90	325	Yes	1 1 foot	1	
		30 3000K	90	300	Yes	1-40 1 foot	40	
		35 3500K	90	330	Yes	5 5 feet	1	
		45 4500K	85	330	No			




### LED-TX24\_\_\_ - \_\_\_-WT

Example: LED-TX2445-1-40-WT

### ORDER NUMBER – 5 LED "L" CONNECTOR

Model	Watts	Color Temp	CRI	Lumens	Title 24	Tape Color
LED-TX24	2W/ft	22 2200K	90	110	No	5L-WT White
		27 2700K	90	130	Yes	
		30 3000K	90	130	Yes	
		35 3500K	90	135	Yes	
		45 4500K	85	135	No	



### LED-TX24\_\_\_ -5L-WT

Example: LED-TX2435-5L-WT

waclighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050




Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

# InvisiLED® Pro 2

## 24V LED Tape Light






### Class 2 Power Supply (Required)

Type		Model	Input	Output	Max Run	Dim	
Remote		<b>EN-2460-RB2-T</b>	120VAC	24VAC / 60W	15 feet	Yes	<i>Includes a 6 foot lead wire</i>
		<b>EN-24100-RB2-T</b>	120VAC	24VAC / 96W	25 feet	Yes	
Plug-in		<b>EN-2460-P-AR-T</b>	120VAC	24VAC / 60W	15 feet	Yes	<i>Includes a 6 foot lead wire</i>
		<b>EN-24100-P-AR-T</b>	120VAC	24VAC / 96W	25 feet	Yes	
Remote 277V		<b>EN-24100-277-RB2-T</b>	277VAC	24VDC / 96W	25 feet	No	<i>Includes a 6 foot lead wire</i>

### Accessories

Aluminum Channel		<b>LED-T-CH</b>	5 feet	<i>Includes a diffuser, two end caps, and five screws</i>
Deep Aluminum Channel		<b>LED-T-CH1</b>	5 feet	<i>Includes a diffuser, two end caps, and five screws</i>
45° Angled Aluminum Channel		<b>LED-T-CH2</b>	5 feet	<i>Includes a diffuser, two end caps, and five screws</i>
Fixed Angle Channel Clip		<b>LED-T-CL3-PT</b>	5 feet	<i>Used to mount any aluminum channel Includes 2 pieces, 4 screws</i>
Adjustable Channel Clip		<b>LED-T-CL2-PT</b>	5 feet	<i>Used to mount any aluminum channel Adjusts 50° from center either way Includes 2 pieces, 4 screws</i>
Retrofit Channel		<b>LED-T-RC</b>	3 feet	<i>Creates fixed curves</i>
Clip		<b>LED-T-CL</b>	10 pcs	<i>Holds the tape from the underside Includes 10 pieces, 10 screws</i>
Curve Clip		<b>LED-T-CL1</b>	10 pcs	<i>Runs over the tape to secure the angled tape Includes 2 pieces, 4 screws</i>

Lead Wire		<b>LED-TC-P-2</b> <b>LED-TC-P-12</b>	2 ft 12 ft	<i>Alternative lengths for plug-in power supplies</i>
Extension Cable		<b>LED-TC-EXT-144</b>	12 ft	<i>Extends distance between a hard wired power supply or wiring box to a tape section</i>
Low Voltage Wiring Box With Feed		<b>LED-TC-B-2</b>	L: 1½ in W: ¾ in H: 7⁄8 in	<i>Neatly houses up to two wires with 2" female feed</i>
Low Voltage Wiring Box		<b>LED-T-B</b>	L: 1½ in W: ¾ in H: 7⁄8 in	<i>Neatly houses up to two wires</i>
Wiring Box With Switch		<b>TB-S</b>	L: 6¼ in W: 1½ in H: 1¼ in	<i>Use when spanning a large gap in a system layout without leaving exposed wiring</i>

Joiner Cable		<b>LED-TC-IC2</b> <b>LED-TC-IC6</b> <b>LED-TC-IC12</b> <b>LED-TC-IC36</b> <b>LED-TC-IC72</b>	2 in 6 in 12 in 36 in 72 in	<i>Connects tape sections</i>
3-Way "Y" Connector		<b>LED-TC-Y</b>		<i>Connects tape sections</i>
4-Way "X" Connector		<b>LED-TC-X</b>		<i>Connects tape sections</i>
"L" Connector		<b>LED-TC-L</b>		<i>Connects tape sections</i>
End cap		<b>LED-TC-EC</b>		<i>1 cut end cap 1 male end cap</i>