



Type IC, Air-Tight, Wet & Plenum

DESCRIPTION

6" Round Recessed LED With Integral
Driver In Connection Box
Commercial Grade Quality With Architectural Design


FEATURES & BENEFITS

2 1/4" Deep - Install Where Ceiling Space Is Limited
Type IC Rated - No Housing Required
CRI 90+ for True Color Rendering
Fast & Easy To Install - Save On Labor
Driver Inside Connection Box - No Junction Box Needed
Armored Cable & Metal Connectors - Open Plenum Rated

MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening With Attached Spring Clips. Ceiling Clearance Required: 2 1/2"

DIMENSIONS: ID 6" OD 7" Cut Out 6" to 6 1/4"



120V TRIAC Dimmable Driver Included



Optional 120V-347V Driver 0-10V Dimmable



Order Separately as Cat # LLL-LD2050TR

ORDERING GUIDE Example: LL6RR - 30K - WH

	CCT	Trim Finish	
LL6RR	-	-	
2700K	27K	WH	White
3000K	30K	ВК	Black
4000K	40K		

LL6RR

6" Round Regressed 2nd Gen Plenum LED 17W

Location:	

SPECIFICATION				
Applications	Recessed Ceiling Mount			
Energy Used	17 W			
Color Temperature	2700 3000 4000			
Light Output	1150 1200 1300			
Halogen Equivalent	100 W			
Beam Angle	90°			
CRI	90 +			
Default Driver Input	120V AC Triac Dimmable			
Optional Driver Input	120V-347V AC 0-10V Dimmable			
Junction Box Wire Capacity	Max 5 No 12 AWG or 8 No 14 AWG			
Power Factor	0.98			
Approved Location	Insulated Ceilings, Open Plenum, Wet			
IP Rating	IP 54			
Air Tight	Yes			
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)			
Projected Life	70% Light Output at 50,000 Hours			
Certification	cULus, Energy Star			
Warranty	10 Year Residential / 5 Year Commercial			

AVAILABLE TRIMS





White

Black

ACCESSORIES

Sold Separately



Armored Low Voltage Extensions 10ft - cat # **MEC10** FT6 / CMP rated, Max 40 ft Allowed



26" Flat Rough-In Plates - cat # RIP6



13" Flat Rough-In Plate - cat # MP6-2



Flanged Plate with Hanger Bars - cat # FRP6

Goof Ring White OD 7 5/8" cat # GR6

COMPLIANCE









Type IC Air-Tight Open Plenum