

HIGHLIGHTS

- UL Listed
- Instant On
- Mercury Free
- Sleek Design
- Available in 27k/30k/40k/50k



LUXRITE LED

A19

SHAPE



A21 14W
DIMMABLE



A19 15W



A19 10W



A19 9W
DIMMABLE

Suitable for
Enclosed
Fixtures



SPECIFICATIONS

LUXRITE

MODEL	LIFE	FLOOD	AVERAGE LIFETIME	INPUT VOLTS	POWER FACTOR	FREQUENCY
ALL	45.7	110°	50000hrs (45.7yrs)	120	>0.95	50-60Hz

		MODEL	DESCRIPTION	WATT	WATT REPLACEMENT	LUMENS	COLOR	DIMMABLE	TEMPERATURE	CRI	CASE	ENERGY STAR	UL LISTED
60 WATT REPLACEMENT	A19 10W	LR21370	LED10A19/27K	10	60	800	2700K	NO	WARM WHITE	80	50		UL
		LR21371	LED10A19/30K	10	60	800	3000K	NO	SOFT WHITE	80	50		UL
		LR21372	LED10A19/40K	10	60	800	4000K	NO	COOL WHITE	80	50		UL
		LR21373	LED10A19/50K	10	60	800	5000K	NO	BRIGHT WHITE	80	50		UL
		LR21376	LED10A19/27K/RP4	10	60	800	2700K	NO	WARM WHITE	80	48		UL
		LR21377	LED10A19/30K/RP4	10	60	800	3000K	NO	SOFT WHITE	80	48		UL
		LR21378	LED10A19/40K/RP4	10	60	800	4000K	NO	COOL WHITE	80	48		UL
		LR21379	LED10A19/50K/RP4	10	60	800	5000K	NO	BRIGHT WHITE	80	48		UL
	DIMMABLE A19 9W	LR21270	LED9A19/D827/E	9	60	800	2700K	YES	WARM WHITE	80	50		UL
		LR21271	LED9A19/D830/E	9	60	800	3000K	YES	SOFT WHITE	80	50		UL
		LR21272	LED9A19/D840/E	9	60	800	4000K	YES	COOL WHITE	80	50		UL
		LR21273	LED9A19/D850/E	9	60	800	5000K	YES	BRIGHT WHITE	80	50		UL
100 WATT REPLACEMENT	A19 15W	LR21071	LED15A19/27K	15	100	1600	2700K	NO	WARM WHITE	80	25		UL
		LR21072	LED15A19/30K	15	100	1600	3000K	NO	SOFT WHITE	80	25		UL
		LR21073	LED15A19/40K	15	100	1600	4000K	NO	COOL WHITE	80	25		UL
		LR21074	LED15A19/50K	15	100	1600	5000K	NO	BRIGHT WHITE	80	25		UL
		LR21075	LED15A19/27K/RP4	15	100	1600	2700K	NO	WARM WHITE	80	24		UL
		LR21076	LED15A19/30K/RP4	15	100	1600	3000K	NO	SOFT WHITE	80	24		UL
		LR21077	LED15A19/40K/RP4	15	100	1600	4000K	NO	COOL WHITE	80	24		UL
		LR21078	LED15A19/50K/RP4	15	100	1600	5000K	NO	BRIGHT WHITE	80	24		UL
	DIMMABLE A21 14W	LR21081	LED14A21/HL/27K	14	100	1500	2700K	YES	WARM WHITE	80	20		UL
		LR21082	LED14A21/HL/30K	14	100	1500	3000K	YES	SOFT WHITE	80	20		UL
		LR21083	LED14A21/HL/40K	14	100	1500	4000K	YES	COOL WHITE	80	20		UL
		LR21084	LED14A21/HL/50K	14	100	1500	5000K	YES	BRIGHT WHITE	80	20		UL