

HIGHLIGHTS

- Energy Star Qualified
- ETL Listed
- Sleek Design
- 50,000 hours
- Easy Installation
- Dimmable
- Available in
10" / 12" / 14" / 16" / 18"
- Available in
3000K, 4000K, 5000K

LUXRITE LED

FLUSH
MOUNT
CHROME
SHAPE



5 Year
Warranty



LUXRITE

SPECIFICATIONS

MODEL	FLOOD	CRI	AVERAGE LIFETIME	INPUT VOLTS	FREQUENCY	DIMMABLE	MERCURY FREE	DAMP LOCATION
ALL	120°	83	50000hrs (45.7yrs)	120	60Hz	●	●	●

MODEL	DESCRIPTION	DIMENSION	COLOR TEMPERATURE	LUMENS	WATT	LUMEN EFFICACY	POWER FACTOR	INPUT CURRENT	ETL	ES
LR23170	LED10"FLUSH/ CHROME/30K/2	10"L*10"W*3"H	3000K SOFT WHITE	1000	14	71.4	0.98	112mA	ETL	ES
LR23171	LED10"FLUSH/ CHROME/40K/2	10"L*10"W*3"H	4000K COOL WHITE	1000	14	71.4	0.98	112mA	ETL	ES
LR23180	LED10"FLUSH/ CHROME/50K/2	10"L*10"W*3"H	5000K BRIGHT WHITE	1000	14	71.4	0.98	112mA	ETL	ES
LR23172	LED12"FLUSH/ CHROME/30K/2	12"L*12"W*3.3"H	3000K SOFT WHITE	1380	18	76.7	0.99	151mA	ETL	ES
LR23173	LED12"FLUSH/ CHROME/40K/2	12"L*12"W*3.3"H	4000K COOL WHITE	1380	18	76.7	0.99	151mA	ETL	ES
LR23181	LED12"FLUSH/ CHROME/50K/2	12"L*12"W*3.3"H	5000K BRIGHT WHITE	1380	18	76.7	0.99	151mA	ETL	ES
LR23174	LED14"FLUSH/ CHROME/30K/2	14"L*14"W*3.45"H	3000K SOFT WHITE	1652	22	75.1	0.9	183mA	ETL	ES
LR23175	LED14"FLUSH/ CHROME/40K/2	14"L*14"W*3.45"H	4000K COOL WHITE	1652	22	75.1	0.9	183mA	ETL	ES
LR23182	LED14"FLUSH/ CHROME/50K/2	14"L*14"W*3.45"H	5000K BRIGHT WHITE	1652	22	75.1	0.9	183mA	ETL	ES
LR23176	LED16"FLUSH/ CHROME/30K/2	16"L*16"W*4.25"H	3000K SOFT WHITE	1960	26	75.4	0.99	223mA	ETL	ES
LR23177	LED16"FLUSH/ CHROME/40K/2	16"L*16"W*4.25"H	4000K COOL WHITE	1960	26	75.4	0.99	223mA	ETL	ES
LR23183	LED16"FLUSH/ CHROME/50K/2	16"L*16"W*4.25"H	5000K BRIGHT WHITE	1960	26	75.4	0.99	223mA	ETL	ES
LR23178	LED18"FLUSH/ CHROME/30K/2	18"L*18"W*4.45"H	3000K SOFT WHITE	2160	30	72.0	0.9		ETL	ES
LR23179	LED18"FLUSH/ CHROME/40K/2	18"L*18"W*4.45"H	4000K COOL WHITE	2160	30	72.0	0.9		ETL	ES
LR23184	LED18"FLUSH/ CHROME/50K/2	18"L*18"W*4.45"H	5000K BRIGHT WHITE	2160	30	72.0	0.9		ETL	ES