

DOWNLIGHT RETROFIT EYEBALL GIMBAL

4", 5-6"



4"



5-6"



SPECIFICATIONS

ELECTRICAL

MODEL	DESCRIPTION	POWER	INPUT VOLTS	DIMMABLE	EFFICACY (LPW)	FREQUENCY	LIFETIME	WATT REPLACEMENT
LR23230	LED/DL4/EB/3000K/FL	10	120V	YES	72.0	60Hz	50,000	50
LR23235	LED/DL4/EB/5000K/FL	10	120V	YES	74.0	60Hz	50,000	50
LR23040	LED/DL5-6/EB/3000K/FL	15	120V	YES	67.0	60Hz	50,000	120
LR23045	LED/DL5-6/EB/5000K/FL	15	120V	YES	71.0	60Hz	50,000	120

PHOTOMETRIC

MODEL	COLOR (CCT)	TEMP	LUMEN	FLOOD	CRI	CASE	COST/YR	BASE TYPE	ETL LISTED	UL LISTED
LR23230	3000K	SOFT WHITE	720	90°	90	12	\$ 1.20	E26 ADAPTER	YES	
LR23235	5000K	BRIGHT WHITE	740	90°	90	12	\$ 1.20	E26 ADAPTER	YES	
LR23040	3000K	SOFT WHITE	1010	90°	90	12	\$ 1.81	E26 ADAPTER		YES
LR23045	5000K	BRIGHT WHITE	1060	90°	90	12	\$ 1.81	E26 ADAPTER		YES

GENERAL

DIAGRAM

