

GIMBAL RECESSED DOWNLIGHT

CCT SELECTABLE ROUND & SQUARE

2", 3" & 4"



COMPATIBLE WITH:

LR35123


EM LED DRIVER



LR23255 • LR23257

LR41002

NEW
CONSTRUCTION
MOUNTING PLATE




LR23236 • LR23241

LR23246 • LR23250

LR41003

NEW
CONSTRUCTION
MOUNTING PLATE



3
Year
Warranty

CRI
80

GIMBAL
SHAPE

DAMP LOCATION
RATED

DIMMABLE*

IC
RATED

120V

SPECIFICATIONS

ELECTRICAL

		MODEL	DESCRIPTION	POWER	INPUT VOLTS	DIMMABLE	EFFICACY	FREQUENCY	WATT REPLACEMENT	LIFETIME
2"		LR23236	LED5W/DL2/GB/5CCT/FL	5	120V	YES	80	50/60Hz	50	50,000
	RD	LR23241	LED8W/DL3/GB/3CCT/RD/BK	8	120V	YES	75	50/60Hz	50	50,000
3"		LR23246	LED8W/DL3/GB/3CCT/FL	8	120V	YES	75	50/60Hz	50	50,000
	SQ	LR23250	LED8W/DL3/GB/3CCT/SQ	8	120V	YES	75	50/60Hz	50	50,000
4"		LR23255	LED11W/DL4/GB/3CCT/RD	11	120V	YES	91	50/60Hz	75	50,000
	RD	LR23257	LED11W/DL4/GB/3CCT/RD/BK	11	120V	YES	91	50/60Hz	75	50,000

PHOTOMETRIC

MODEL	COLOR (CCT)	TEMP	LUMEN	FLOOD	CRI	FINISH	DAMP LOCATION	COST/YR	ETL LISTED	ENERGY STAR
LR23236	2700K/3000K/3500K/4000K/5000K	WARM/SOFT/NATURAL/COOL/BRIGHT	400	40°	80	WHITE	YES	\$ 0.60	YES	YES
LR23241	3000K/4000K/5000K	SOFT/COOL/BRIGHT	600	40°	80	BLACK	YES	\$ 0.96	YES	
LR23246	3000K/4000K/5000K	SOFT/COOL/BRIGHT	600	40°	80	WHITE	YES	\$ 0.96	YES	YES
LR23250	3000K/4000K/5000K	SOFT/COOL/BRIGHT	600	40°	80	WHITE	YES	\$ 0.96	YES	YES
LR23255	3000K/4000K/5000K	SOFT/COOL/BRIGHT	1000	40°	80	WHITE	YES	\$ 1.32	YES	YES
LR23257	3000K/4000K/5000K	SOFT/COOL/BRIGHT	1000	40°	80	BLACK	YES	\$ 1.32	YES	

DIMENSIONS

