

HIGHLIGHTS

- Sleek Design
- High Lumen
- 50,000 hours
- UL Listed
- Available in 2x2 & 2x4 version
- Available in 3000K, 3500K & 4000K
- 0-10v Dimming

LUXRITE LED

CENTER
BASKET
TROFFER

SHAPE



LUXRITE

SPECIFICATIONS

MODEL	CASE	FLOOD	AVERAGE LIFETIME	VOLTS	OPERATING TEMPERATURE
ALL	1	120°	50000hrs (45.7yrs)	100 - 277	-4° - 122°

	MODEL	DESCRIPTION	WATT	LUMENS	COLOR	TEMPERATURE	LUMEN EFFICACY	UL
2'X2'	LR24200	LED35W2X2TROFFER/CB/30K	37	4100	3000K	SOFT WHITE	110	UL
	LR24201	LED35W2X2TROFFER/CB/35K	35	4000	3500K	NATURAL WHITE	114	UL
	LR24202	LED35W2X2TROFFER/CB/40K	35	4000	4000K	COOL WHITE	114	UL
2'X4'	LR24205	LED60W2X4TROFFER/CB/30K	60	6600	3000K	SOFT WHITE	110	UL
	LR24206	LED60W2X4TROFFER/CB/35K	60	6700	3500K	NATURAL WHITE	111	UL
	LR24207	LED60W2X4TROFFER/CB/40K	60	6800	4000K	COOL WHITE	113	UL

DIMENSIONS

