

LED SPOTLIGHT-CANLESS

3" REGRESSED INTERCHANGEABLE TRIM MODULE

CCT SELECTABLE - HIGH OUTPUT 38°, 60°



3" MODULE



LR25105



LR25106


INTERCHANGEABLE TRIMS

*SOLD SEPARATELY


LR25107



LR25108



LR25109



CRI
90

COLOR SELECTABLE

2700K 3000K 3500K 4000K 5000K

DIMMABLE

TRIAC

IC
RATED

HIGH
OUTPUT

AIR
TIGHT

WET
LOCATION
RATED

5
YEAR
WARRANTY

ELECTRICAL

	MODEL	DESCRIPTION	POWER	INPUT VOLTS	EFFICACY	FLOOD	LIFETIME	COST/YR
3"	LR25105	LED/DLMD3HO/FL/5CCT/D2	15	120V	83	38°	50,000	\$ 1.80
	LR25106	LED/DLMD3HO/WFL/5CCT/D2	15	120V	83	60°	50,000	\$ 1.80

PHOTOMETRIC

MODEL	DESCRIPTION	COLOR (CCT)	TEMP	LUMEN	CRI	ETL LISTED	PLATE (KNOCKOUT)
LR25105	LED/DLMD3HO/FL/5CCT/D2	2700K/3000K/3500K/4000K/5000K	CCT SELECT	1250	90	YES	LR41002 (#0) LR41006 (#1) LR41010 (RO)
LR25106	LED/DLMD3HO/WFL/5CCT/D2	2700K/3000K/3500K/4000K/5000K	CCT SELECT	1250	90	YES	


INTERCHANGEABLE TRIMS



LR25107



LR25108



LR25109


	MODEL	DESCRIPTION	FINISH
ROUND	LR25107	LED/DLMD3HO/TRIM/RD/W2	ROUND WHITE
SQUARE	LR25108	LED/DLMD3HO/TRIM/SQ/W2	SQUARE WHITE
ROUND	LR25109	LED/DLMD3HO/TRIM/RD/BK2	ROUND BLACK

COMPATIBLE
WITH:


LR35126
Emergency
LED Driver




LR41002
New Construction
Mounting Plate



LR41010
New Construction
Mounting Plate



LR41006
New Construction
Mounting Plate



120-277V DRIVER

*SOLD SEPARATELY

	MODEL	DESCRIPTION	POWER	INPUT
15W	LR23418	LED/URDL2/DRIVER/UNV/O-10V	15	120-277V



DIMENSIONS

