

LED SLIM LINEAR


**3 CCT & WATTAGE SELECT
HIGH OUTPUT
4', 8'**



8' (96")



4' (48")



**CCT & WATTAGE SELECT
SWITCH ON THE SIDE**

COMPATIBLE WITH:

**LR35120
LR35121**

EM LED DRIVER



**5
Year
Warranty**

**CRI
82**

**LINEAR
FIXTURE
SHAPE**

**CCT
NATURAL
3500K
COOL
4000K
BRIGHT
5000K**

**DAMP LOCATION
RATED**

**DIMMABLE*
0-10V**

120-277V

SPECIFICATIONS

ELECTRICAL

	MODEL	DESCRIPTION	POWER	COLOR	LUMEN	EFFICACY	INPUT VOLTS	DIMMABLE	FREQUENCY	LIFETIME
48"	LR25185	LED48/LINEAR/3CCT/3WO/UNV/D/HO	34W	3500K	4726	139	120-277V	0-10V	50/60Hz	50,000
				4000K	4760	140				
				5000K	4794	141				
			38W	3500K	5168	136				
				4000K	5206	137				
				5000K	5244	138				
			45W	3500K	5985	133				
				4000K	6030	134				
				5000K	6075	135				
96"	LR25187	LED96/LINEAR/3CCT/3WO/UNV/D/HO	65W	3500K	9035	139	120-277V	0-10V	50/60Hz	50,000
				4000K	9100	140				
				5000K	9165	141				
			75W	3500K	10200	136				
				4000K	10275	137				
				5000K	10350	138				
			90W	3500K	11970	133				
				4000K	12060	134				
				5000K	12150	135				

PHOTOMETRIC

MODEL	COLOR (CCT)	TEMP	CRI
LR25185	3500K/4000K/5000K	NATURAL/COOL/BRIGHT	82
LR25187	3500K/4000K/5000K	NATURAL/COOL/BRIGHT	82

GENERAL

OPERATING TEMP.	CASE SIZE	DAMP LOCATION	UL LISTED	DLC LISTED
-4° - 122°	9	YES	YES	YES
-4° - 122°	4	YES	YES	YES

DIMENSIONS

