

HIGHLIGHTS

- UNIVERSAL :
BALLAST COMPATIBLE /
BYPASS BALLAST
- 120-277 Input Volt
- High Efficacy > 100 LPM
- Shatter Proof, PET
Covered Glass Tube
- 50,000Hr Long Life
- ETL Listed
- DLC Listed

LUXRITE LED

UNIVERSAL
GLASS
LED TUBE
SHAPE



3 Year
Warranty



LUXRITE

SPECIFICATIONS

MODEL	SUB TYPE	BASE	CASE	FINISH	CRI	AVERAGE LIFETIME	FLOOD
ALL	BYPASS+DIRECT	G13	25	SHATTERPROOF	83	50000hrs (45.7yrs)	240°

MODEL	DESCRIPTION	WATT	LUMENS	COLOR TEMPERATURE		MOL	LUMEN EFFICIENCY	WATT REPLACEMENT	ETL	DLC
LR34070	LED12T8/30K/24/SG/UNV	12	1100	3000K	SOFT WHITE	24"	100.0	17	ETL	
LR34071	LED12T8/35K/24/SG/UNV	12	1100	3500K	NATURAL	24"	100.0	17	ETL	
LR34072	LED12T8/40K/24/SG/UNV	12	1100	4000K	COOL WHITE	24"	100.0	17	ETL	
LR34073	LED12T8/50K/24/SG/UNV	12	1100	5000K	BRIGHT WHITE	24"	100.0	17	ETL	
LR34074	LED12T8/65K/24/SG/UNV	12	1100	6500K	DAYLIGHT	24"	100.0	17	ETL	
LR34075	LED16T8/30K/36/SG/UNV	16	1600	3000K	SOFT WHITE	36"	100.0	25	ETL	
LR34076	LED16T8/35K/36/SG/UNV	16	1600	3500K	NATURAL	36"	100.0	25	ETL	
LR34077	LED16T8/40K/36/SG/UNV	16	1600	4000K	COOL WHITE	36"	100.0	25	ETL	
LR34078	LED16T8/50K/36/SG/UNV	16	1600	5000K	BRIGHT WHITE	36"	100.0	25	ETL	
LR34079	LED16T8/65K/36/SG/UNV	16	1600	6500K	DAYLIGHT	36"	100.0	25	ETL	
LR34180	LED18T8/30K/48/SG/UNV	18	2000	3000K	SOFT WHITE	48"	111.1	32	ETL	DLC
LR34181	LED18T8/35K/48/SG/UNV	18	2100	3500K	NATURAL	48"	116.7	32	ETL	DLC
LR34182	LED18T8/40K/48/SG/UNV	18	2100	4000K	COOL WHITE	48"	116.7	32	ETL	DLC
LR34183	LED18T8/50K/48/SG/UNV	18	2200	5000K	BRIGHT WHITE	48"	122.2	32	ETL	DLC
LR34184	LED18T8/65K/48/SG/UNV	18	2200	6500K	DAYLIGHT	48"	122.2	32	ETL	DLC

DIRECT

Working with Ballast



BYPASS

Directly AC Input

