



White Color:

UPC Code: 078477254189 Country Of Origin: China



Available Colors:



M58AA-W

Tamper-Resistant USB Receptacle, Type A/A, 20 Amp 125 Volt, Commercial Grade, White - Lev-Lok

Lev-Lok Combination Tamper-Resistant Duplex Decora Receptacle and Dual-Port USB Type A-A Charger, NEMA 5-20R, 20A-125V, 2 Pole, 3-Wire Grounding Receptacle -White

Lev-Lok employs a simple twist and lock wiring module to provide a safe and secure connection. These devices are pre-wired for 3x faster installations and 5x faster swap outs than traditional wiring. The speed and ease of Lev-Lok allows for optimal time, labor, and cost savings. The M58AA:

- Two Type A USB ports with a combined total of 3.6A of charging power, the fastest in the industry
- Type A USBs are the most recognized and commonly used USB port, used in most desktops, laptops, tablets, etc.
- Common applications: health care facilities, lobbies & waiting rooms, airports, hospitality, and educational institutions
- For use with MSTWL Lev-Lok wiring modules only, modules sold separately

Technical Information

Electrical Specifications Amperage: 20 A

Current Interrupting: Certified for full-

rated current and voltage Dielectric Voltage: 2000 VAC Grounding: Self-Grounding Horsepower Rating: 1 hp

Temperature Rise: Max 30°C

Voltage: 125 VAC

Wire: 3

Environmental Specifications Flammability: Rated V-0 per UL 94 Operating Temperature: Maximum Continuous 40°C, Minimum -10°C (w/o

impact)

Material Specifications

Body Material: PBT Face Material: Thermoplastic **Ground Clips:** Brass **Ground Contacts: Brass**

Locking Pins: Solid Brass Mounting Screws: #6 Plated Steel Mounting Strap: Galvanized Steel

Shutter Material: Thermoplastic Shutter Mechanism: Acetal

Mechanical Specifications

Product ID: Ratings are marked on

device

Strap Construction: Through-Strap

Termination: Modular

Product Features Brand: Lev-Lok Color: White

Device Type: Combination Device Feature: USB Type A, Tamper-

Resistant

Grade: Commercial Specification Grade

NEMA: 5-20R **USB Specifications**

Single Port Charging Power: 12W Total Charging Power: 18W **USB Cable Compatible:** Type A

USB Charger: 3.6A

Standards & Certifications

Applicable Standards: UL 498, CSA C22.2, No. 42, UL 1310, UL 94, NOM, FCC Class B

NEMA: WD-1 and WD-6

Warranty

Warranty: 5-Year Limited

CA2621644	US7357652
CA2624409	US7666010
CA2655707	US7820909
CA2667092	US7868719
CA2677283	US8096818
CN200880004760.2	US8242362
MX338817	US9368982
US7355117	US9496726

^{*}This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:temperature} \textbf{Telephone: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

