









PROJECT NAME:	CAT. #:
NOTES:	FIXTURE SCHEDULE:

Architectural Wall Sconce

CCT Selectable



Product Description:

The LED Wall Sconce provides long-lasting illumination with a decorative touch to corridors in hotels, motels and commercial property applications. It offers long life, high lumen maintenance, and dimmable operation for residential and commercial applications that exceed those of a traditional bulb fixture.

Features:

- 2700/3000/4000K CCT selectable
- Even light distribution

Dimming:

• 120V Triac Dimming

Construction:

- Steel Construction
- · Powder coated finish

Listings:

- · cETLus listed for Indoor, Damp locations
- FCC

Ordering Information

FAMILY	SUB FAMILY	STYLE	FINISH	VOLTAGE	WATTAGE	ССТ
ML9= Wall Sconce	LA= LED Integrated	A= Architectural	BN= Brushed Nickel	[BLANK]= 120V, Triac dimming	23= 23W	CS= 80CRI, 2700/3000/4000K

Stocked Items


MODEL NUMBER	ORDER CODE
ML9LAABN23CS	106083

Specifications	ML9LAABN23CS
Power Consumption	23W
Lumens Delivered (Im)	2,070 lm
Efficacy (lm/W)	90
CRI	≥80
CCT (K)	2700/3000/4000K
L70 Lifetime (hrs)	≥50,000
Voltage	120V
Power Factor	≥0.9
Operating Temperature	-4°F to 104°F (-20°C to 40°C)
Listings	cETLus, FCC
Environment	Suitable for damp locations
Warranty	5 Years

Dimming Compatibility

DIMMER MODELS			
	Leviton	DVCL-153PR-WH, CTCL-153PDH-WH, R62-06674-P0W, R12-06672-1LW, R50-IPL06-10M	
	Lutron	TGCL-153PH-WH, MACL-153MH-WH, P-PKG1W-WH-R	
	Eaton	AAL06-C1, SAL06P-LA-K	

Dimensions







5-year standard warranty (further details available at www.maxlite.com/warranties)

Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.