

Project:	Туре:
Prepared By:	Date:

**Driver Info LED** Info Watts 7W Input Voltage 12V Color Temp 2700K (Soft White) Power Factor 0.9 <45% 450 Flicker Lumens 69.2 LPW THDi N/A Efficacy Color Accuracy 80 CRI R9 L70 Accuracy 25,000

## **Technical Specifications**

Listings

UL Listed:

Yes

FCC:

Yes

Rohs:

Yes

CEC Status:

Not lawful for sale in California

**ENERGY STAR V2.0:** 

This product is ENERGY STAR® Version 2.0 Certified

**Energy Star ID:** 

2329293

Description

Dimmable:

Yes, down to 20%

Lamp Type:

Mini-reflector

**Bulb Type:** 

MR16

Base Type:

GU5.3

Material:

Plastic

Construction

**Operating Temparture:** 

-20 - 45°C

MOL (inches):

1.81"

MOD (inches):

1.97"

**LED Characteristics** 

Lifespan:

25,000-hour LED lifespan based on IES LM-70 results

Other

Equivalent:

35W Halogen MR16

Warranty:

3 years

Optical

Beam Angle:

35°

MBCP:

700

## **Technical Specifications (continued)**

**Shipping Information** 

Case Qty:

12


**Case Dimensions:** 7.68 x 5.71 x 2.56

Pallet Quantity of Pieces:

2064

**Pallet Dimensions:** 

47.83 x 39.96 x 10.24



## **Features**

SMALL REFLECTOR REPLACEMENT - Replaces conventional small-reflector lamps

ENERGY SAVINGS - Save up to 85% on energy

25,000-HOUR LIFESPAN - Long-life product

DAMP RATED - Suitable for damp locations

DIMMABLE - Compatible with most common dimmer models

80 CRI - Ideal for general lighting applications

Ordering Matr	rix					
Family	,	Lamp Power	CRI	Color Temp	Beam Angle	Dimmable
MR16	6	6	8	27	35D	DIM
		6 = 50W 8 = 50W	8 = 80 CRI	27 = 2700K 30 = 3000K 50 = 5000K	<b>25D =</b> 25 degrees <b>35D =</b> 35 degrees	<b>DIM =</b> Dimmable