

MS303-DSW

30 Amp, 600 Volt, 3-Pole, Three-Phase Single Throw AC Manual Motor Controller, Suitable as Motor Disconnect, Standard Toggle, Industrial Grade, Non-Grounding, Back & Side Wiring - White



UPC Code : 078477983720

Country Of Origin : Mexico

RoHS Compliant : Yes

Available Colors :



Black

Technical Information

AC Horsepower Ratings

HP Rating : 3HP-120V, 7.5HP-240V, 15HP-480V, 20HP-600V

Electrical Specifications

Amperage : 30 A

Dielectric Voltage : Withstands 2200 VAC for 1 min.

Endurance : 6,000 cycles inductive motor type load

Grounding : Non-Grounding

Pole : 3

Temperature Rise : 50°C Max at full rated current

Voltage : 600 VAC

Environmental Specifications

Flammability : Rated V-0 per UL 94

Operating Temperature : -40°C to 60°C

Overload UL20 Test : 50 cycles at 6 times full rated current

Short Circuit Current Rating : 10,000 RMS symmetrical amps at 600V AC max. when protected by a 30A time delay fuse

Material Specifications

Base Material : Thermoplastic Polyester

Contacts : Silver-Cadmium .031 Thick

Cover Material : Thermoplastic Polyester

Face Material : Thermoplastic Polyester

Strap Material : Nickel-Plated Brass

Terminal Screws : Nickel-Plated Brass 10-32, Triple Combination

Toggle : Thermoplastic Polyester

Mechanical Specifications

Product ID : Ratings are permanently marked on device

Terminal Accom. : #10-#8 AWG

Terminal ID : T1, T2, T3, L1, L2 & L3 marked on back of device

Termination : Back & Side

Torque Range : 20 inch pounds maximum

Product Features

Color : White

Device Type : Toggle Switch

Standards and Certifications

ANSI : C-73



NEMA : WD-1 & WD-6

NOM : NOM-ANCE

UL 60947-4-1 : supersedes UL 508

Warranty : 10-Year Limited

cUL per CSA C22.2 No. 111 : File #E63969




MS302-DS Shown (Dimensions same for MS302-DSW,
MS303-DS, MS303-DSW)

Wiring Diagram

3-Pole

Line/Ligne/Línea
600V AC/c.a./CA, 30A



SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):
+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-
1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

