

MT-4LD3 - 3 Light

4" LED Precision Multiples Energy Star®

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Retractable, adjustable spot lights

FEATURES

- ELV and 0-10V dimming options
- Energy Star® rated
- Invisible Trim™ is designed to sit flush with the ceiling for a clean, architectural look
- Fully retractable from housing
- 365° horizontal rotation and 180° vertical aiming
- Accepts 1 replacement lens
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Die-cast aluminum heat sink painted black. Trim, housing and junction box are 20 gauge steel. Frame and hanger bars are heavy gauge galvanized steel.

J-Box: Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: Universal (120V - 277V) or 120V input only

Light Source: High output LED (included with housing)



Dimming: 0-10V or ELV (see list of housings below)

Mounting: Supplied with hanger bars, adjustable from 14½"-25" to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surface up to 1" thick. 14½" × 5½" cutout with trim, 14½" × 5½" cutout for Invisible Trim™. See instruction sheet for details on installation using spackle ring.

Finish: Abrasion resistant powder coat paint in Black (BK).

Standards: ETL & cETL listed.


TRIMS

		MT-4LD316T Trim	WT White BK Black
		MT-4LD316TL Invisible Trim™	WT White



Example: **MT-4LD316T-BK**

HOUSINGS

	Power	Beam	Color Temp	CRI	Interior
	MT-4LD316N 0-10V dimming Non-IC, 120V-277V input	16.5W			
	MT4LD316NE ELV dimming Non-IC, 120V input	16.5W			
	MT4LD311NE ELV dimming IC-Rated, 120V input	11.5W			
		S 20° F 40°	27 2700K 85 927 2700K 90 30 3000K 85 930 3000K 90 35 3500K 85 40 4000K 85		BK Black



Example: **MT-4LD316NE-S927-BK**

REPLACEMENT LENS

Amber	LENS-16-AMB
Blue	LENS-16-BLU
Green	LENS-16-GRN
Red	LENS-16-RED
Yellow	LENS-16-YEL

UV Filter	LENS-16-UVF
Frosted	LENS-16-FR
Spread	LENS-16-SPR
Beam Elongator	LENS-16-BEL

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center







1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585

MT-4LD3 - 3 Light

4" LED Precision Multiples Energy Star®

WAC LIGHTING
Responsible Lighting®

LUMINAIRE PERFORMANCE	Power	Beam	Photometry	Color Temp	CRI	Lumen	CBCP
MT-4LD316N 0-10V dimming Non-IC, 120V-277V input	16.5W	S 20°		27 2700K 85 2760 4490 x 3 927 2700K 90 2370 3605 x 3 30 3000K 85 2880 4790 x 3 930 3000K 90 2445 3910 x 3 35 3500K 85 2925 4720 x 3 40 4000K 85 3300 5370 x 3			
		F 40°		27 2700K 85 2715 2015 x 3 927 2700K 90 2355 1615 x 3 30 3000K 85 2820 2090 x 3 930 3000K 90 2400 1705 x 3 35 3500K 85 2880 2110 x 3 40 4000K 85 3240 2390 x 3			
		S 20°		27 2700K 85 2805 4506 x 3 927 2700K 90 2280 3545 x 3 30 3000K 85 2916 4630 x 3 930 3000K 90 2670 4170 x 3 35 3500K 85 3015 4700 x 3 40 4000K 85 2955 4700 x 3			
		F 40°		27 2700K 85 2880 1955 x 3 927 2700K 90 2250 1605 x 3 30 3000K 85 2940 2110 x 3 930 3000K 90 2700 1890 x 3 35 3500K 85 2970 2095 x 3 40 4000K 85 2955 2115 x 3			
MT4LD311NE ELV dimming IC-Rated, 120V input	11.5W	S 20°		27 2700K 85 2295 3315 x 3 927 2700K 90 1860 2685 x 3 30 3000K 85 2055 3575 x 3 930 3000K 90 1905 2795 x 3 35 3500K 85 2400 3550 x 3 40 4000K 85 2670 3925 x 3			
		F 40°		27 2700K 85 2295 1670 x 3 927 2700K 90 1830 1270 x 3 30 3000K 85 2295 1590 x 3 930 3000K 90 1875 1295 x 3 35 3500K 85 2355 1640 x 3 40 4000K 85 2655 1820 x 3			

WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center
1750 Archibald Avenue • Ontario, CA 91760
Phone (800) 526.2588 • Fax (800) 526.2585