NATL-5100HW

24V Class II Non-Dimmable Hardwire LED Driver

Source: 100-240V Input / 24V Output

81.6W

PRODUCT DESCRIPTION

24V enclosed driver to be used with Nora Lighting's 24 Volt systems.

FEATURES

- · Non-dimmable
- · Conduit access wiring compartment
- · Meet Class II output limits
- · 24V DC rated output
- · Includes 10' power line connector (NALTL-10)
- · cULus listed enclosure & cULus recognized driver

ELECTRICAL

Input Voltage: 100-240V Output Voltage: 24VDC Wattage: 81.6W Dimming: Non-Dimmable

COMPATIBLE NORA 24V SYSTEMS

LED Drivers are compatible with Nora Lighting's 24V systems

ELD DITIONS OF COMPANDIC WITH NOTA LIGHTING 3 2 IV SYSTEMS	
SERIES	DESCRIPTION
NMP2-A	24V Josh Adjustable
NMP2-LE	24V Josh Fixed
NUTP1	24V Standard Tape Light (Silicone Encapsulated
NUTP5	24V Hy-Brite Tape Light
NUTP7	24V Standard Tape Light (Non-Encapsulated)
NUTP8	24V High Output Tape Light
NUTP9	24V Side-Lit Tape Light
NUTP10	24V CCT Color Changing Tape Light
NUTP14	24V COB High Output Tape Light
NUTP51	24V Continuous Hy-Brite Tape Light
NUTP71	24V Continuous Standard Tape Light
NUTP81	24V Continuous High Output Tape Light
NULB	24V Lightbar Silk SBC

OPTIONAL ACCESSORIES

NALTL-10: 10' Power Line Connector (included)

NALTL-30: 30' Power Line Connector

NATL-302W: Power Line Splitter, white cable. Splits power line connector into two separate connections.

LABELS AND LISTINGS

- cULus Listed
- · FCC compliant










PRODUCT IMAGES & DIMENSIONS

Notes



NATL-5100HW 24V Class II Non-Dimmable Hardwire LED Driver



NALTL-10 / NALTL-30 Power Line Connector (10' included)



NATL-302W Power Line Splitter

NATL-302W = Power Line Splitter, White

24V Class II Non-Dimmable Hardwire LED Driver Optional Accessories Output Voltage / Wattage Description NATL-5100HW = 24V Ouput / 81.6W NALTL-10 = 10' Power Line Connector (included w/each driver) NALTL-30 = 30' Power Line Connector



Example: NATL-5100HW = 24V 81.6W Class II Non-Dimmable Hardwire LED Driver