



UL Copper Grounding Busbars

Grounding Busbars are insulated ground bus mounting plates.

The Type 110 alloy solid copper ground bar are 1/4" thick and stand 2-1/2" from the backboard or wall.

12" accepts 9 lugs

24" accepts 21 lugs

Accepting lugs with either 3/4", 1" or 1-3/4" centers.

Any lug with 3/8" bolts may be used.



Each Busbar consists of:

- Busbar
- (2) Insulators
- (2) Standoff Brackets
- (4) Stainless Steel Bolts
- (4) Lock Washers
- (4) Flat Washers

PART #	DESCRIPTION
GB1-6	1" x 6" x 1/4" CU Ground Bar
GB1-12	1" x 12" x 1/4" CU Ground Bar
GB2-6	2" x 6" x 1/4" CU Ground Bar
GB2-8	2" x 8" x 1/4" CU Ground Bar
GB2-12	2" x 12" x 1/4" CU Ground Bar
GB2-18	2" x 18" x 1/4" CU Ground Bar
GB2-24	2" x 24" x 1/4" CU Ground Bar
NAV-GB4-6	4" x 6" x 1/4" CU Ground Bar
NAV-GB4-12	4" x 12" x 1/4" CU Ground Bar
GB4-18	4" x 18" x 1/4" CU Ground Bar w/Assembly
GB4-18NH	4" x 18" x 1/4" CU Ground Bar No Holes w/Mtg. Brkt.
GB4-24	4" x 24" x 1/4" CU Ground Bar
GB4-36	4" x 36" x 1/4" CU Ground Bar w/Insulator
GB4-STANDOFF	4" Ground Bar Mounting Bracket - SS



**155 Marcus Blvd.
Hauppauge, NY 11788
Phone: 718.272.4222
www.navtechny.com**

