



DISCONNECT SWITCH

**3 POLE, 200 AMP, INDOOR FUSIBLE GENERAL DUTY
SAFETY SWITCH**

PART# NAV-SS-200-3-F

FEATURES

- Designed for residential and light commercial applications where duty is not severe
- Listed per UL Standard 98, Enclosed and Dead Front Switches
- UL Service Entrance rated when installed in accordance with the National Electrical Code
- Meets NEMA Enclosed Switch Standard KS1-1990 for Type General Duty
- 200 AMP fusible switches are rated 10,000 rms amps. sym IC when used with Class K or H fuses
- NEMA 1 LINE TOP/LOAD BOTTOM construction for indoor use
- Laser Prefabbed knockouts standard on bottom, top, rear and sides of cabinet
- Shed roof equipped to prevent water intrusion through front cover
- Pad-lockable in off position
- Active safety latch keeps cover closed when switch is in on position
- 60°C and 75°C conductor rating



SPECIFICATION



Number of Poles	3
Wire	4
Ampere Rating (A)	200
Volts (V)	240
Enclosure Type	Indoor
Type of Duty	General Duty
Disconnect Type	Fusible
Action	Single Throw
Wire Range (CU/AL)	(1) #6-250 or (2) #10-#1
Height (IN.)	31-1/4"
Width (IN.)	13"
Depth (IN.)	5-1/2"
Standards	UL Listed