



## Disconnect Switch Part# NAV-SS-400-3-F

*3 POLE, 400 AMP, INDOOR, FUSIBLE,  
GENERAL DUTY SAFETY SWITCH*

### **Features**

- Designed for residential and light commercial applications where duty is not severe
  - Listed per UL Standard 98, Enclosed and Dead Front Switches
  - UL Service Entrance rated when installed in accordance with the National Electrical Code
  - Meets NEMA Enclosed Switch Standard KS1-1990 for Type General Duty
  - Features quick-make, quick-break mechanisms (30-200 amps)
  - 60°C and 75°C conductor rating
  - 30-200 AMP fusible switches are rated 100,000 rms amps, sym IC when used with Class R fuses. Refer to BuyLog to order appropriate Class R Fusing Kit
  - Bottom-feed version available for 200-600 amp, NEMA 1 only
- Fusible and Non-Fusible switches available(consult BuyLog for interrupt ratings)

### **Specification**

Number of Poles	3
Wire	4
Ampere Rating (A)	400
Volts (V)	240
Enclosure Type	Indoor
Type of Duty	General Duty
Disconnect Tupe	Fusible
Action	Single Throw
Wire Range (CU/AL)	(1) 2-600 or (2) 1/0-250 (1) 2-600 or (2) 1/0-250
Height (IN.)	49.5
Width (IN.)	22
Depth (IN.)	9
Standards	UL Listed

155 Marcus Blvd.  
Hauppauge, NY 11788  
718.257.2111  
**www.NavTechNY.com**



8/2022