


NL-4870

Fully Adjustable Elbow with Square Trim

TRIM DIMENSIONS



Width/Length: 5"
Height: 3-1/4"
Maximum Extension: 5-3/4"

FEATURES

Trim

Metal trim with fully adjustable elbow can be adjusted up 358° horizontally and 70° vertically. Adjustable elbow allows lamp to be front loaded into trim.

Mounting

Trim includes two butterfly clips that securely mount trim in housing.

Compatible Housings

Compatible with Low Voltage housings.

See individual specification sheets for more information.

Lamp

Low Voltage

20W-75W 12V MR16 (NL-401 Series; NL-402 Series; NLIC-401 Series; NLIC-402 Series; NLR-403 Series; NLR-404 Series; NLR-405 Series)

Labels and Listings

cULus Listed for Damp Location when used with compatible housing.

Fully Adjustable Elbow with Square Trim

NL-4870B: Black Fully Adjustable Elbow with Black Square Trim

NL-4870BZ: Bronze Fully Adjustable Elbow with Bronze Square Trim

NL-4870C: Chrome Fully Adjustable Elbow with Chrome Square Trim

NL-4870CO: Copper Fully Adjustable Elbow with Copper Square Trim

NL-4870G: Gold Fully Adjustable Elbow with Gold Square Trim

NL-4870N: Natural Metal Fully Adjustable Elbow with Natural Metal Square Trim

NL-4870W: White Fully Adjustable Elbow with White Square Trim

NORALIGHTING.

Type

Project

Catalog No.

Lamp/Wattage

Compatible Housings

LOW VOLTAGE

NL-401QAT/20	Non-IC AT New Const., Mag.	20W MR16	W: 6" L: 9" H: 5-1/2"
NL-401QAT/37	Non-IC AT New Const., Mag.	37W MR16	W: 6" L: 9" H: 5-1/2"
NL-401QAT	Non-IC AT New Const., Mag.	50W MR16	W: 6" L: 9" H: 5-1/2"
NL-401/50/277AT	Non-IC AT New Const., Mag.	50W MR16	W: 6" L: 9" H: 5-1/2"
NL-401AT/1EL	Non-IC AT New Const., Elec.	50W MR16	W: 6" L: 9" H: 5-1/2"
NL-401AT/2EL	Non-IC AT New Const., Elec.	50W MR16	W: 6" L: 9" H: 5-1/2"
NL-401/75	Non-IC AT New Const., Mag.	75W MR16	W: 7" L: 11-1/2" H: 6-3/8"
NL-401/75/277	Non-IC AT New Const., Mag.	75W MR16	W: 7" L: 11-1/2" H: 6-3/8"
NL-401/75/1EL	Non-IC AT New Const., Elec.	75W MR16	W: 7" L: 11-1/2" H: 6-3/8"
NL-401/75/2EL	Non-IC AT New Const., Elec.	75W MR16	W: 7" L: 11-1/2" H: 6-3/8"
NL-402S/20	Non-IC Shallow New Con., Mag.	20W MR16	W: 6" L: 8-1/2" H: 3-1/2"
NL-402S/37	Non-IC Shallow New Con., Mag.	37W MR16	W: 6" L: 8-1/2" H: 3-1/2"
NL-402S	Non-IC Shallow New Con., Mag.	50W MR16	W: 6" L: 8-1/2" H: 3-1/2"
NL-402S/1EL	Non-IC Shallow New Con., Elec.	50W MR16	W: 6" L: 8-1/2" H: 3-1/2"
NLIC-401QSAT/20	IC Air-Tight New Const., Mag.	20W MR16	W: 7-3/4" L: 12-1/2" H: 7-1/4"
NLIC-401QSAT/37	IC Air-Tight New Const., Mag.	37W MR16	W: 7-3/4" L: 12-1/2" H: 7-1/4"
NLIC-401QSAT	IC Air-Tight New Const., Mag.	50W MR16	W: 7-3/4" L: 12-1/2" H: 7-1/4"
NLIC-401AT/277V	IC Air-Tight New Const., Mag.	50W MR16	W: 10-3/4" L: 17-3/4" H: 7-1/2"
NLIC-401AT/1EL	IC Air-Tight New Const., Elec.	50W MR16	W: 7-3/4" L: 12-1/2" H: 7-1/4"
NLIC-401AT/2EL	IC Air-Tight New Const., Elec.	50W MR16	W: 7-3/4" L: 12-1/2" H: 7-1/4"
NLIC-402QSAT/20	IC Air-Tight Shallow NC, Mag.	20W MR16	W: 13-1/8" L: 14" H: 5-3/8"
NLIC-402QSAT/37	IC Air-Tight Shallow NC, Mag.	37W MR16	W: 13-1/8" L: 14" H: 5-3/8"
NLIC-402QSAT	IC Air-Tight Shallow NC, Mag.	50W MR16	W: 13-1/8" L: 14" H: 5-3/8"
NLIC-402AT/1EL	IC Air-Tight Shallow NC, Elec.	50W MR16	W: 13-1/8" L: 14" H: 5-3/8"
NLR-403S/20	Non-IC Shallow Remodel, Mag.	20W MR16	W: 4-7/8" L: 13-1/2" H: 3-1/2"
NLR-403S/37	Non-IC Shallow Remodel, Mag.	37W MR16	W: 4-7/8" L: 13-1/2" H: 3-1/2"
NLR-403S	Non-IC Shallow Remodel, Mag.	50W MR16	W: 4-7/8" L: 13-1/2" H: 3-1/2"
NLR-403S/1EL	Non-IC Shallow Remodel, Elec.	50W MR16	W: 4-7/8" L: 11-3/4" H: 3-1/2"
NLR-404QAT/20	Non-IC Air-Tight Remodel, Mag.	20W MR16	W: 4-7/8" L: 14-1/2" H: 5-5/8"
NLR-404QAT/37	Non-IC Air-Tight Remodel, Mag.	37W MR16	W: 4-7/8" L: 14-1/2" H: 5-5/8"
NLR-404QAT	Non-IC Air-Tight Remodel, Mag.	50W MR16	W: 4-7/8" L: 14-1/2" H: 5-5/8"
NLR-404/50/277	Non-IC Air-Tight Remodel, Mag.	50W MR16	W: 4-7/8" L: 14-1/2" H: 5-5/8"
NLR-404AT/1EL	Non-IC Air-Tight Remodel, Elec.	50W MR16	W: 4-7/8" L: 14-1/2" H: 5-5/8"
NLR-404AT/2EL	Non-IC Air-Tight Remodel, Elec.	50W MR16	W: 4-7/8" L: 14-1/2" H: 5-5/8"
NLR-404/75	Non-IC Remodel, Magnetic	75W MR16	W: 4-7/8" L: 14-1/2" H: 6-3/8"
NLR-404/75/277	Non-IC Remodel, Magnetic	75W MR16	W: 4-7/8" L: 14-1/2" H: 6-3/8"
NLR-404/75/1EL	Non-IC Remodel, Electronic	75W MR16	W: 4-7/8" L: 14-1/2" H: 6-3/8"
NLR-404/75/2EL	Non-IC Remodel, Electronic	75W MR16	W: 4-7/8" L: 14-1/2" H: 6-3/8"
NLR-405AT/20	Non-IC Air-Tight Remodel	20W MR16	W: 4-3/4" L: 4-3/4" H: 4-1/4"
NLR-405AT/37	Non-IC Air-Tight Remodel	37W MR16	W: 4-3/4" L: 4-3/4" H: 4-1/4"
NLR-405AT	Non-IC Air-Tight Remodel	50W MR16	W: 4-3/4" L: 4-3/4" H: 4-1/4"

NORALIGHTING.

6505 Gayhart St., Commerce, CA 90040
www.noralighting.com • Specifications subject to change without notice. © 2011
Phone: 800.686.6672 • FAX: 800.500.9955 • e-mail: nora@noralighting.com