

## NLCBC2-4 COBALT Click Series - 4" 97 CRI Recessed Retrofit Downlight

Source: 12W 750Lm LED

### PRODUCT DESCRIPTION

Nora Lighting's patent pending 4" LED Cobalt Click Luminaires are cULus listed for use in existing 4" IC or Non-IC housings manufactured by Nora and others. The units provide 750 Lumen output, drawing 12W and rendering 97 CRI. Nora's 4" Cobalt LEDs integrate the latest from the Cree® COB family of LED arrays, giving bright spectacular light output and low power consumption. An obvious and smart choice for green energy efficient lighting in commercial and residential applications.

### FEATURES

- 5-Year limited warranty
- CREE® COB LED
- Dimmable
- cULus Listed, ENERGY STAR® and Title 24 compliant
- 750lm utilizes only 12W
- Available in 2700K, 3000K and 4000K color temperature, 97 CRI
- GU24 Socket adapter available for use with GU24 base housings
- Includes Medium-Base Socket kit

### CONSTRUCTION

UTM thermal management features an integral driver, large heat sink and the latest Cree COB technology. The patent pending "Click" system allows the aluminum spun trims to be easily changed in the field. Trims are easily interchanged with the help of spring mounting clips which properly secure them to the LED module. Various trim styles are available in both square and round options.

### RETROFIT

Cobalt Series Downlights include NRA-211 Medium Base screw-in socket for retrofitting into existing Medium Base downlight housings.

### ELECTRICAL SYSTEM

**Voltage:** 120VAC

**Current:** 300mA

**Power Consumption:** 12 Watts

**Light Source:** Cree COB

**Lumens:** 750 lm

**CRI:** 97 CRI

**LED Driver:** Built-in driver


**Operating Temperature:** 0°C to 75°C ambient temperature

**Life Expectancy:** 50,000 hours

### Dimmable

Dimmable to 10% (Varies by Dimmer). [Click Here](#) or refer to [www.NoraLighting.com](http://www.NoraLighting.com) for compatible dimmer list in the "Compatibility" page under "Resources" tab.

### DIMENSIONS



### LABELS & LISTINGS

cULus Listed for Wet Location  
Title 24 Compliant  
ENERGY STAR® Rated



### 4" Cobalt Click Recessed Retrofit Downlight

Catalog No.	Trim Style	Color Temp.	Finish (See below)	Option (see below)
<b>NLCBC2-</b>	<b>451</b> = Reflector	<b>27</b> = 2700K	<b>BB</b> = Black	
	<b>452</b> = Baffle	<b>30</b> = 3000K	<b>BW</b> = Black/White	
	<b>453</b> = Square Round	<b>35</b> = 3500K	<b>BZBZ</b> = Bronze	
	<b>456</b> = Square Regressed	<b>40</b> = 4000K	<b>COCO</b> = Copper	
	<b>4501</b> = Reflector (Wall Wash)		<b>DW</b> = Diffused/White	
	<b>4502</b> = Baffle (Wall Wash))		<b>HZW</b> = Haze/White	
			<b>NN</b> = Natural Metal	
			<b>WW</b> = White	
		<b>PW</b> = Pewter (Square Reg. Only)		

	BB	BW	BZBZ	COCO	DW	HZW	NN	PW	WW
451	•	•	•	•	•	•	•	•	•
452	•	•	•	•	•	•	•	•	•
453			•		•	•			•
456	•	•	•			•	•	•	•
4501	•	•	•	•	•	•	•		•
4502			•						•

(Blank) 120V Triac Dimming  
LE2 277V Non Dimming  
LE4 120V 0-10V / 120V Triac / 277V 0-10V Dimming  
EM Emergency  
LE4EM LE4 Dimming w/Emergency

### COMPATIBLE HOUSINGS

<b>FireBox</b>	
<b>NFBIC-4INCAT</b>	4" ICAT 2-Hour Fire Rated
<b>NFBIC-4LMRAT</b>	4" ICAT Dedicated LED 2-Hour Fire Rated
<b>New Construction</b>	
<b>NSIC-401QAT</b>	4" ICAT Line Voltage
<b>NS-401QAT</b>	4" AT Line Voltage
<b>NHIC-4G24AT</b>	4" ICAT GU24 (Specify NRA-212 adaptor separately)
<b>NHIC-4LMRAT</b>	4" ICAT Dedicated LED
<b>NHIC-4LMRAT/277</b>	4" ICAT Dedicated LED, 277V
<b>NHIC-4LMRAT/4W</b>	4" ICAT Dedicated LED for LE4
<b>NHIC-4LMRAT/EM</b>	4" ICAT Dedicated LED w/Battery and Test Switch
<b>Remodel</b>	
<b>NSR-404QAT</b>	4" AT Line Voltage
<b>NSRIC-404QAT</b>	4" ICAT Line Voltage
<b>NHRIC-4G24AT</b>	4" ICAT GU24 (Specify NRA-212 adaptor separately)
<b>NHRIC-4LMRAT</b>	4" ICAT Dedicated LED

**Example: NLCBC2-45630WW** 4" Cobalt Click Square Regressed LED Retrofit unit, 3000K, White Reflector, White Flange

## NLCBC2-5 COBALT Click Series - 5" 97 CRI Recessed Retrofit Downlight

Source: 12W 750Lm LED

### PRODUCT DESCRIPTION

Nora Lighting's patent pending 5" LED Cobalt Click Luminaires are cULus listed for use in existing 5" IC or Non-IC housings manufactured by Nora and others. The units provide 750 Lumen output, drawing 12W and rendering 97 CRI. Nora's 4" Cobalt LEDs integrate the latest from the Cree® COB family of LED arrays, giving bright spectacular light output and low power consumption. An obvious and smart choice for green energy efficient lighting in commercial and residential applications.

### FEATURES

- 5-Year limited warranty
- CREE® COB LED
- Dimmable
- cULus Listed, ENERGY STAR® and Title 24 compliant
- 750lm utilizes only 12W
- Available in 2700K, 3000K and 4000K color temperature, 97 CRI
- GU24 Socket adapter available for use with GU24 base housings
- Includes Medium-Base Socket kit

### CONSTRUCTION

UTM thermal management features an integral driver, large heat sink and the latest Cree COB technology. The patent pending "Click" system allows the aluminum spun trims to be easily changed in the field. Trims are easily interchanged with the help of spring mounting clips which properly secure them to the LED module. Various trim styles are available in both square and round options.

### RETROFIT

Cobalt Series Downlights include NRA-211 Medium Base screw-in socket for retrofitting into existing Medium Base downlight housings.

### ELECTRICAL SYSTEM

**Voltage:** 120VAC

**Current:** 300mA

**Power Consumption:** 12 Watts

**Light Source:** Cree COB

**Lumens:** 750 lm

**CRI:** 97 CRI

**LED Driver:** Built-in driver


**Operating Temperature:** 0°C to 75°C ambient temperature

**Life Expectancy:** 50,000 hours

### Dimmable

Dimmable to 10% (Varies by Dimmer). [Click Here](#) or refer to [www.NoraLighting.com](http://www.NoraLighting.com) for compatible dimmer list in the "Compatibility" page under "Resources" tab.

### DIMENSIONS



### LABELS & LISTINGS

cULus Listed for Wet Location  
Title 24 Compliant  
ENERGY STAR® Rated



### 5" Cobalt Click Recessed Retrofit Downlight

Catalog No.	Trim Style	Color Temp.	Finish (See below)	Option (see below)
NLCBC2-	551 = Reflector	27 = 2700K	BB = Black	
	552 = Baffle	30 = 3000K	BW = Black/White	
	553 = Square Round	35 = 3500K	BZBZ = Bronze	
	556 = Square Regressed	40 = 4000K	COCO = Copper	
	5501 = Reflector (Wall Wash)		DW = Diffused/White	
	5502 = Baffle (Wall Wash)		HZW = Haze/White	
			NN = Natural Metal	
			WW = White	
			PW = Pewter (Square Reg. Only)	

	BB	BW	BZBZ	COCO	DW	HZW	NN	PW	WW
551	•	•	•	•	•	•	•	•	•
552	•	•	•	•	•	•	•	•	•
553	•	•	•	•	•	•	•	•	•
556	•	•	•	•	•	•	•	•	•
5501	•	•	•	•	•	•	•	•	•
5502	•	•	•	•	•	•	•	•	•

(Blank) 120V Triac Dimming  
LE2 277V Non Dimming  
LE4 120V 0-10V / 120V Triac / 277V 0-10V Dimming  
EM Emergency  
LE4EM LE4 Dimming w/Emergency

### COMPATIBLE HOUSINGS

#### FireBox

NFBIC-5INCAT 5" ICAT 2-Hour Fire Rated  
NFBIC-5LMRAT 5" ICAT Dedicated LED 2-Hour Fire Rated

#### New Construction

NH-501Q 5" Line Voltage  
NHIC-501QAT 5" ICAT Line Voltage  
NHIC-527QAT 5" ICAT Shallow Line Voltage  
NHIC-5G24ATFL 5" ICAT GU24 (Specify NRA-212 adaptor separately)  
NHIC-5LMRAT 5" ICAT Dedicated LED  
NHIC-527LMRAT 5" ICAT Shallow Dedicated LED  
NHIC-5LMRAT/4W 5" ICAT Dedicated LED for LE4  
NHIC-5LMRAT/EM 5" ICAT Dedicated LED w/Battery and Test Switch

#### Remodel

NHR-504Q 5" Line Voltage  
NHR-504QAT 5" AT Line Voltage  
NHRIC-527QAT 5" ICAT Shallow Line Voltage  
NHRIC-5G24ATFL 5" ICAT GU24 (Specify NRA-212 adaptor separately)  
NHRIC-5LMRAT 5" ICAT Dedicated LED  
NHRIC-527LMRAT 5" ICAT Shallow Dedicated LED

Example: NLCBC2-55630WW 5" Cobalt Click Square Regressed LED Retrofit unit, 3000K, White Reflector, White Flange

## NLCBC2-6 COBALT Click Series - 6" 97 CRI Recessed Retrofit Downlight

Source: 12W 750Lm LED

### PRODUCT DESCRIPTION

Nora Lighting's Patent pending 6" LED Cobalt Click Luminaires are cULus listed for use in existing 6" IC or Non-IC housings manufactured by Nora and others. The units provide 750 Lumen output, drawing 12W and rendering 97 CRI. Nora's 6" Cobalt LEDs integrate the latest from the Cree® COB family of LED arrays, giving bright spectacular light output and low power consumption. An obvious and smart choice for green, energy efficient lighting in commercial and residential applications.

### FEATURES

- 5-Year limited warranty
- CREE® COB LED
- Dimmable
- cULus Listed, ENERGY STAR® and Title 24 compliant
- 750lm utilizes only 12W
- Available in 2700K, 3000K and 4000K color temperature, 97 CRI
- GU24 Socket adapter available for use with GU24 base housings
- Includes Medium-Base Socket kit

### CONSTRUCTION

UTM thermal management features an integral driver, large heat sink and the latest Cree COB technology. The patent pending "Click" system allows the aluminum spun trims to be easily changed in the field. Trims are easily interchanged with the help of spring mounting clips which properly secure them to the LED module. Various trim styles are available in both square and round options.

### RETROFIT

Cobalt Series Downlights include NRA-211 Medium Base screw-in socket for retrofitting into existing Medium Base downlight housings.

### ELECTRICAL SYSTEM

**Voltage:** 120VAC

**Current:** 300mA

**Power Consumption:** 12 Watts

**Light Source:** Cree COB

**Lumens:** 750 lm

**CRI:** 97 CRI

**LED Driver:** Built-in driver


**Operating Temperature:** 0°C to 75°C ambient temperature

**Life Expectancy:** 50,000 hours

### Dimmable

Dimmable to 10% (Varies by Dimmer). [Click Here](#) or refer to [www.NoraLighting.com](http://www.NoraLighting.com) for compatible dimmer list in the "Compatibility" page under "Resources" tab.

### DIMENSIONS



### LABELS & LISTINGS

cULus Listed for Wet Location  
Title 24 Compliant  
ENERGY STAR® Rated



### 6" Cobalt Click Recessed Retrofit Downlight

Catalog No.	Trim Style	Color Temp.	Finish (See below)	Option (see below)
NLCBC2-	651 = Reflector	27 = 2700K	BB = Black	
	652 = Baffle	30 = 3000K	BW = Black/White	
	653 = Square Round	35 = 3500K	BZ = Bronze	
	656 = Square Regressed	40 = 4000K	CO = Copper	
	6501 = Reflector (Wall Wash)		DW = Diffused/White	
			HZW = Haze/White	
	6502 = Baffle (Wall Wash)		NN = Natural Metal	
			WW = White	
			PW = Pewter (Square Reg. Only)	

	BB	BW	BZBZ	COCO	DW	HZW	NN	PW	WW
51	•	•	•	•	•	•	•	•	•
52	•	•	•	•	•	•	•	•	•
53	•	•	•	•	•	•	•	•	•
56	•	•	•	•	•	•	•	•	•
501	•	•	•	•	•	•	•	•	•
502	•	•	•	•	•	•	•	•	•

(Blank)	120V Triac Dimming
LE2	277V Non Dimming
LE4	120V 0-10V / 120V Triac / 277V 0-10V Dimming
EM	Emergency
LE4EM	LE4 Dimming w/Emergency

### COMPATIBLE HOUSINGS

FireBox	6" ICAT 2-Hour Fire Rated
NFBIC-6INCAT	6" ICAT Dedicated LED 2-Hour Fire Rated
NFBIC-6LMRAT	
New Construction	
NH-26Q	6" Line Voltage
NH-26Q	6" Line Voltage (No Bracket)
NHIC-17QAT	6" ICAT Line Voltage
NHIC-17QNBAT	6" ICAT Line Voltage (No Bracket)
NHIC-27QAT	6" ICAT Shallow Line Voltage
NHIC-6G24ATFL	6" ICAT GU24 (Specify NRA-212 adaptor separately)
NHIC-6LMRAT	6" ICAT Dedicated LED
NHIC-27LMRAT	6" ICAT Shallow Dedicated LED
NHIC-6LMRAT/4W	6" ICAT Dedicated LED for LE4
NHIC-6LMRAT/EM	6" ICAT Dedicated LED w/Battery and Test Switch
Remodel	
NHR-26Q	6" Line Voltage
NHIC-17QAT	6" ICAT Line Voltage
NHIC-17QNBAT	6" ICAT Line Voltage (No Bracket)
NHIC-27QAT	6" ICAT Shallow Line Voltage
NHIC-6G24ATFL	6" ICAT GU24 (Specify NRA-212 adaptor separately)
NHIC-6LMRAT	6" ICAT Dedicated LED
NHIC-27LMRAT	6" ICAT Shallow Dedicated LED

Example: NLCBC2-65630WW 6" Cobalt Click Square Regressed LED Retrofit unit, 3000K, White Reflector, White Flange