

UNIT

ITEM NO.

PRICE

DESCRIPTION

STD PKG QTY

STD PKG WT

ARCHITECTURAL VERTICAL CFL FRAME-INS

RECESSED
& STEP LIGHT

MLS SERIES


SPECIALTY

TRACK &
MINI TRACK

RAIL

GLASS, PENDANT
& SCANCES

EXIT &
EMERGENCY

TRANSFORMER
DRIVER & LAMP


Bar Hangers sold
separately, see
page 232

NHPV-613EL
NHPV-613EL/EM
NHPV-613EL/EMI
NHPV-613 *

6" 13W Vertical Architectural Frame-In, Electronic, 120-277V 4 22
6" 13W Vertical Arch. Frame-In, Electronic, 120-277V Emerg. Ballast, Remote Test Switch
6" 13W Vertical Arch. Frame-In, Electronic, 120-277V Emerg. Ballast, Integral Test Switch
6" 13W Vertical Architectural Frame-In, Electronic, Dimmable
* Dimming options: D10, M7

NHPV-618EL
NHPV-618EL/EM
NHPV-618EL/EMI
NHPV-618 *


6" 18W Vertical Architectural Frame-In, Electronic, 120-277V
6" 18W Vertical Arch. Frame-In, Electronic, 120-277V Emerg. Ballast, Remote Test Switch
6" 18W Vertical Arch. Frame-In, Electronic, 120-277V Emerg. Ballast, Integral Test Switch
6" 18W Vertical Architectural Frame-In, Electronic, Dimmable
* Dimming options: D10, MX1, MX2, M7, ECO, L11, L12

NHPV-62642EL
NHPV-62642EL/EM
NHPV-62642ELEMI
NHPV-62642 *

6" 26-42W Vertical Architectural Frame-In, Electronic, 120-277V
6" 26-42W Vert. Arch. Frame-In, Electronic, 120-277V Emerg. Ballast, Remote Test Switch
6" 26-42W Vert. Arch. Frame-In, Electronic, 120-277V Emerg. Ballast, Integral Test Switch
6" 26-42W Vertical Architectural Frame-In, Electronic, Dimmable
* Dimming options: DAS, D10, MX1, MX2, M7, ECO, L11, L12

- Length: 13"; Width: 11-3/8"; Depth: 10-1/2"; Ceiling Opening: 6-3/8"
- Special universal mounting bracket accepts 1/2" EMT, C-Channel, T-bar fasteners and bar hangers (not included), adjustable 3" vertically from above or below ceiling

COMMERCIAL VERTICAL CFL FRAME-INS



Includes
Bar Hangers

NHPV-13EL
NHPV-13EL/EM
NHPV-13EL/EMI
NHPV-13 *

6" 13W Vertical Commercial Frame-In, Electronic, 120-277V 4 22
6" 13W Vertical Com. Frame-In, Electronic, 120-277V Emerg. Ballast, Remote Test Switch
6" 13W Vertical Com. Frame-In, Electronic, 120-277V Emerg. Ballast, Integral Test Switch
6" 13W Vertical Commercial Frame-In, Electronic, Dimmable
* Dimming options: D10, M7

NHPV-18EL
NHPV-18EL/EM
NHPV-18EL/EMI
NHPV-18 *


6" 18W Vertical Commercial Frame-In, Electronic, 120-277V
6" 18W Vertical Com. Frame-In, Electronic, 120-277V Emerg. Ballast, Remote Test Switch
6" 18W Vertical Com. Frame-In, Electronic, 120-277V Emerg. Ballast, Integral Test Switch
6" 18W Vertical Commercial Frame-In, Electronic, Dimmable
* Dimming options: D10, MX1, MX2, M7, ECO, L11, L12

NHPV-2642EL
NHPV-2642EL/EM
NHPV-2642EL/EMI
NHPV-2642 *

6" 26-42W Vertical Commercial Frame-In, Electronic, 120-277V
6" 26-42W Vert. Com. Frame-In, Electronic, 120-277V Emerg. Ballast, Remote Test Switch
6" 26-42W Vert. Com. Frame-In, Electronic, 120-277V Emerg. Ballast, Integral Test Switch
6" 26-42W Vertical Commercial Frame-In, Electronic, Dimmable
* Dimming options: DAS, D10, MX1, MX2, M7, ECO, L11, L12

- Length: 13"; Width: 11-3/8"; Depth: 10-1/2"; Ceiling Opening: 6-3/8"
- Includes 24-1/2" Hanger Bars with captive nails, T-Bar Slot and alignment foot

ARCHITECTURAL VERTICAL CFL REMODEL



NHRPV-613EL
NHRPV-613 *

6" 13W Vertical Architectural Remodel, Electronic, 120-277V 1 4
6" 13W Vertical Architectural Remodel, Electronic, Dimmable
* Dimming options: D10, M7

NHRPV-618EL
NHRPV-618 *

6" 18W Vertical Architectural Remodel, Electronic, 120-277V
6" 18W Vertical Architectural Remodel, Electronic, Dimmable
* Dimming options: D10, MX1, MX2, M7, ECO, L11, L12

NHRPV-62642EL
NHRPV-62642 *

6" 26-42W Vertical Architectural Remodel, Electronic, 120-277V
6" 26-42W Vertical Architectural Remodel, Electronic, Dimmable
* Dimming options: DAS, D10, MX1, MX2, M7, ECO, L11, L12

- Length: 11-1/4"; Width: 7"; Depth: 10"; Ceiling Opening: 6-3/8"

SERIES FEATURES

FEATURE:

- Frame-In accepts High Performance Reflectors for Quad or Triple Tube
- Class P integral fluorescent electronic ballast with universal voltage 120-277V
- Keep 3" from insulation
- J-box includes quick connects
- Lamp: (1) 13W to 42W 4-Pin Quad or Triple Tube
- cULus listed for damp locations and feed through
- cULus listed for wet location when used with lensed trims



* DIMMING OPTIONS: SEE PAGE 74-75 FOR DIMMING BALLAST INFORMATION. CONTACT YOUR LOCAL REP FOR PRICING. THE DIMMING CONTROL SYSTEM IS REQUIRED TO VERIFY COMPATIBILITY.