

NOX-432

4" Onyx Round Retrofit Baffle

Source: 10.5W or 14.5W LED
650lm or 900lm

PRODUCT DESCRIPTION

Onyx Retrofit Series is suitable for use with most 4" recessed housings. Die-cast aluminum construction provides clean sharp edges. Deep regressed optics and round aperture delivers even and glare-free illumination. Available in multiple color temperatures and 90+ CRI.

FEATURES

- 650lm / 10.5W or 900lm / 14.5W
- 3500K, 4000K or 5000K @ 90+ CRI
- Integral dimmable driver
- Includes medium base socket adapter for easy retrofitting in 4" recessed housings
- Quick connector is compatible with dedicated LED housings
- 5-year limited warranty
- cULus classified for wet locations
- ENERGY STAR certified

SPECIFICATION

Reflector: One piece, die-cast aluminum construction dissipates heat and extends life. Unitized Thermal Management, UTM, provides exceptional cool operation.

Mounting: Two steel, spring mounting blades allow for easy and secure mounting in most 4" housings.

Optics: Nora specified and designed precision-molded lens for optimal lumen output and even distribution. The white polymer lens diffuser evenly distributes the light.

Retrofit: Onyx retrofit series includes medium base screw-socket adapter ([NRA-21ISM](#)) for retrofitting into existing medium base downlight housings. GU24 socket adapter is available for use with GU24 housings, must specify [NRA-212SM](#).

ELECTRICAL

Input Voltage: 120V

Lumens / Wattage:

(blank) = 650lm / 10.5W; /9 = 900lm / 14.5W

Color Temperature: 3500K, 4000K or 5000K

Color Rendering Index: 90+CRI

Operating Temperature: 0°C to 45°C

Dimming: 5% with electronic low voltage dimmer
or 10% with 2-wire dimmer

[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

COMPATIBLE HOUSINGS

Onyx reflectors are compatible with most 4" IC and Non-IC housings by Nora and others.

Fire Box

- [NFBC-4LMRATA*](#) IC Air-Tight Dedicated LED Firebox
- [NFBC-427LMRATA*](#) Shallow ICAT Dedicated LED Firebox
- [NFBC-4INCATA](#) IC Air-Tight Line Voltage Firebox

New Construction

- [NHIC-4LMRAT*](#) IC Air-Tight Dedicated LED
- [NHIC-4LMRAT/277*](#) ICAT Dedicated LED, 277V
(includes step-down transformer)
- [NHICCP-4LMRAT*](#) Chicago Plenum Dedicated LED
(NHICCP-4LMRAT is not compatible with 900lm)
- [NHIC-427LMRAT*](#) Shallow IC Air-Tight Dedicated LED
(NHIC-427LMRAT is not compatible with 900lm)
- [NSIC-401QAT](#) IC Air-Tight Line Voltage
- [NS-401QAT](#) Air-Tight Line Voltage
- [NHIC-4G24AT](#) IC Air-Tight GU24

Remodel

- [NHRIC-4LMRAT*](#) IC Air-Tight Dedicated LED
- [NHRIC-427LMRAT*](#) Shallow IC Air-Tight Dedicated LED
(NHRIC-427LMRAT is not compatible with 900lm)
- [NSR-404QAT](#) Air-Tight Line Voltage

* Nora LED Dedicated housings are cULus listed for use only with Nora LED Retrofits.

ACCESSORIES

- [NOX-4EYELIDW](#): Round eyelid used to convert round reflector or baffle to half moon wall wash trim.
- [NOX-4OR-W](#): Round oversize ring used to cover ceiling cut-outs up to 5-3/8".

LABELS AND LISTINGS

- cULus classified for Wet Locations
- ENERGY STAR certified
- [5-Year Limited Warranty](#)
- Meets ASTM-E283 Air-Tight requirements
- Certified to the high efficacy requirements of California Title 24 JA8-2022



Type

Project

Catalog No.

Notes

PRODUCT IMAGES AND DIMENSIONS





NOX-432
Round Baffle



NOX-432 / NOX-4EYELIDW
White Eyelid



NOX-432 / NOX-4OR-W
White Oversize Ring



4" Onyx Round Retrofit Baffle

Lumens / Wattage / Color Temperature

- [NOX-43227WW](#) = 650lm / 10.5W / 2700K (Discontinued, direct replacement: [NOXAC-43227WW/HL](#))
- [NOX-43227WW/9](#) = 900lm / 14.5W / 2700K (Discontinued, direct replacement: [NOXAC-43227WW/HL](#))
- [NOX-43230WW](#) = 650lm / 10.5W / 3000K (Discontinued, direct replacement: [NOXAC-43230WW/HL](#))
- [NOX-43230WW/9](#) = 900lm / 14.5W / 3000K (Discontinued, direct replacement: [NOXAC-43230WW/HL](#))
- [NOX-43235WW](#) = 650lm / 10.5W / 3500K
- [NOX-43235WW/9](#) = 900lm / 14.5W / 3500K
- [NOX-43240WW](#) = 650lm / 10.5W / 4000K
- [NOX-43240WW/9](#) = 900lm / 14.5W / 4000K
- [NOX-43250WW](#) = 650lm / 10.5W / 5000K
- [NOX-43250WW/9](#) = 900lm / 14.5W / 5000K

Optional Accessories

Description

- NOX-4EYELIDW** = 4" Round Eyelid, White
- NOX-4OR-W** = 4" Round Oversize Ring, White
- NRA-21ISM** = Medium base screw-in socket (included w/ ea)
- NRA-212SM** = Socket adapter for use with GU24 housings

Example: **NOX-43250WW** = 4" Onyx Baffle, 650lm / 10.5W LED, 5000K, White Reflector / White Finish