


NS-42 / NS-43 / NS-44
NS-46 / NS-52 / NS-53
Reflector with Ring

TRIM DIMENSIONS



Trim OD: 5"
 Aperture: 3-1/2"
 Height: 2"

FEATURES

Trim

Precision spun 0.050 aluminum high grade reflector. Separate trim ring available in metal, may also be used with custom combination of plastic or metal ring finishes.

Mounting

Trim includes three trim clips that securely mount trim in housing.

Compatible Housings

Compatible with Line Voltage, Compact Fluorescent, and GU24 Compact Fluorescent housings. See individual specification sheets for more information.

Lamp

Line Voltage

50W R20/PAR20 Max. (NS-401QAT; NSIC-401QAT; NSR-404QAT)

Compact Fluorescent

13W Quad/Triple (NS-406Q; NS-406EL; NSR-408Q; NSR-408EL)

GU24 Compact Fluorescent

13W-26W GU24 (NHRIC-4G24AT, NHRIC-4G24AT)

Labels and Listings

cULus Listed for Damp Location when used with compatible housing.

Reflector with Ring

- NS-42:** Specular Gold Reflector with White Metal Ring
- NS-42G:** Specular Gold Reflector with Gold Metal Ring
- NS-43:** Specular Black Reflector with White Metal Ring
- NS-43B:** Specular Black Reflector with Black Metal Ring
- NS-44:** Specular Clear Reflector with White Metal Ring
- NS-44C:** Specular Clear Reflector with Chrome Metal Ring
- NS-44HZ:** Haze Reflector with White Metal Ring
- NS-44N:** Specular Clear Reflector with Natural Metal Ring
- NS-46:** Specular White Reflector with White Metal Ring
- NS-52:** Natural Metal Reflector with Natural Metal Ring
- NS-53:** Copper Reflector with Copper Metal Ring
- NS-53BZ:** Bronze Reflector with Bronze Metal Ring

NORALIGHTING.

Type

Project

Catalog No.

Lamp/Wattage

Compatible Housings

LINE VOLTAGE

Item Number	Installation Type	Lamp	Dimensions
NS-401QAT	Non-IC Air-Tight New Const.	50W R/PAR20	W: 5-5/8" L: 8-1/2" H: 5-5/8"
NSIC-401QAT	IC Air-Tight New Construction	50W R/PAR20	W: 5-1/4" L: 8-1/2" H: 6-3/8"
NSR-404QAT	Non-IC Air-Tight Remodel	50W R/PAR20	W: 4-1/4" L: 11-1/4" H: 5-5/8"

COMPACT FLUORESCENT

NS-406Q	Non-IC New Constr., Magnetic	13W Quad	W: 6-1/4" L: 10" H: 5-1/2"
NS-406EL	Non-IC New Constr., Electronic	13W Quad/Triple	W: 6-1/4" L: 9" H: 5-1/2"
NSR-408Q	Non-IC Remodel, Magnetic	13W Quad	W: 4-3/4" L: 11-7/8" H: 5-1/2"
NSR-408EL	Non-IC Remodel, Electronic	13W Quad/Triple	W: 4-3/4" L: 11-7/8" H: 5-1/2"

GU24 COMPACT FLUORESCENT

NHRIC-4G24AT	IC Air-Tight New Construction	13W-26W GU24	W: 6-1/4" L: 13-1/4" H: 6-3/8"
NHRIC-4G24AT	IC Air-Tight Remodel Housing	13W-26W GU24	W: 4-1/4" L: 13" H: 6-3/8"

NORALIGHTING.

6505 Gayhart St., Commerce, CA 90040
 www.noralighting.com • Specifications subject to change without notice. © 2011
 Phone: 800.686.6672 • FAX: 800.500.9955 • e-mail: nora@noralighting.com