OAE Economical Unit Heater













Features

Color

• Standard: almond.

Finish

• Standard: epoxy/polyester powder paint.

Voltage

• 240/208V, 1-phase.

Construction

- 20-gauge steel.
- Adjustable louvers to control warm air flow. 1
- High-limit temperature control with automatic reset (first level) and single operation thermal fuse (second level).

Fan

- 300 cfm fan (51 dBA).
- Totally enclosed factory-lubricated motor. 3

Heating element

- Helical coil nickel-chromium alloy wire protected by ceramic insulators. 4
- Heating element provides instant heat.

Control

• Built-in thermostat included.

Installation

• Wall or ceiling mounting using the supplied brackets which allow 360° rotation of the heater and prevent it from tipping over.

Warranty

• 3-year warranty against defects.

Application

· Garage, workshop.

Models

Product # ¹	Volts	Watts	BTU/hr	Weight	
				lb	kg
OAEU2000AM-EO-TB6	240/208	2000/1500	6824/5118	20.0	9.1
OAEU3000AM-EO-TB6	240/208	3000/2250	10236/7677	20.0	9.1
OAEU5000AM-EO-TB6	240/208	5000/3750	17060/12795	20.0	9.1

¹ Mounting brackets included. Standard color is almond.





