



PAR-C4TIR

4 Megapixel TVI/AHD/CVBS, Outdoor Turret
Smart 65' IR Range, D-WDR, 12VDC

Features

- 4 Megapixel Resolution
- TVI/AHD/CVBS Output
- Fixed Lens
- True Day/Night
- Digital Wide Dynamic Range
- 65' Smart IR Range
- UTC Function
- IP66 Weather Resistant
- 12VDC Operation
- Through InVid Tech DVR:
Free App, CMS & MAC Client

Mounting Options



IPM-DRPM1: Pendant Mount #1
Must be used with IPM-JB4



IPM-TXWM1: Wall Mount #1



IPM-JB4
Junction Box #4

Ordering Information

PAR-C4TIR28: 4 Megapixel Turret, 2.8mm

Image Sensor	1 / 3 "CMOS
Resolution	4MP
Image Size	2560 x 1440
Video Output	TVI/AHD/CVBS Output (must use Paramount DVR to change back once switched from TVI output)
Image System	PAL / NTSC
Electronic Shutter	Auto; 1 / 25s ~ 1 / 50000s (PAL); 1 / 30s ~ 1 / 50000s (NTSC)
IR Distance	65' (20M)
Frame Rate	30fps (60Hz), 25fps (50Hz)
Min. Illumination	0 Lux (IR ON)
Lens	2.8mm
Lens Mount	M12
S / N Ratio	≥52dB (AGC OFF)
Ingress Protection	IP66
Function Control	OSD/UTC
Day & Night	Yes (ICR)
WDR	Digital WDR
Digital NR	Yes (2D DNR)
AGC	Yes
Auto White Balance	Yes
BLC/HLC	Yes
Edge Brightness Compensation	Yes
Defogging	Yes
Sharpness	Yes
Mirror Image	Yes
Smart IR	Yes
Image Setting	Yes
Defect Correction	Auto / Manual
Language	13 different languages
Angle Adjustment	Any angle
Power Supply	DC 12V (± 10%)
Power Consumption	Day : < 1W; Night : < 3W
Working Environment	-4° ~ 122° F (-20° ~ 50° C) 10%~90% Humidity
Dimensions	Ø 3.42 x 4.25" (Ø87 x 108mm)