

Project: Type: Prepared By: Date:



Features and Benefits

Energy efficient replacement for incandescent and halogen PAR lamps

Constructed from durable materials which lowers risk of breakage

Rated for use in enclosed and open fixtures in wet locations

Single optic and full face lens for precise beam angle control

 $Longer\,life span\,compared\,to\,legacy\,equivalents\,minimizes\,replacement\,and\,maintenance\,costs$

ENERGY STAR Compliant, UL Listed

Dimmable down to 20% (check dimmer compatibility list)

Technical Specifications

Performance

Product Type:

PAR

Input Wattage:

11W

Lumens (Nominal):

800lm

Efficacy:

73 lm/W

Color Accuracy (CRI):

80 CRI

L70 Lifespan:

25,000 Hours

Dimmable:

Yes, down to 20%

Construction

Bulb Shape:

PAR30S

Base Type:

E26

Beam Angle:

40°

For Use Outdoors in Open Fixtures:

Yes

Other

Equivalency:

75W Halogen

Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of four (4) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <a href="mailto:rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-trans-rable-t

LED Characteristics

Color Temperature:

3000K Warm White

Electrical

Power Factor:

0.7

Operating Temperature:

-20°C - 45°C

Input Voltage:

120V



Technical Specifications (continued)

Electrical Characteristics

ENERGY STAR V2.0:

CEC Status:

Flicker: <30%

This product is ENERGY STAR® Version 2.0 Certified

Energy Star ID:

2330108

Not lawful for sale in California

Compliance

UL Listed: Yes

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	16.1	12.2	4.4
PALLET	2304	44.5	36.5	47.7

Dimension



