



UPC Code : 078477380956

Country Of Origin : United States

## PT500

2-Gang, 5-Inch Poke-Through Device

5" Diameter Poke-Through Device With Protective Cover. 2-Body Design, Adjustable Anchors, And Standard NPS Threaded Openings.

- **Ease of Installation:** Two-piece construction allows the device to self-level up to 4 degrees
- **Superior Performance:** Adjustable hardened steel anchoring clips securely lock unit inside a cored hole, while allowing for easy removals for inspections, adjustments, repairs, etc.
- **Maximum Compatibility:** Accommodates standard or Decora™ single or duplex receptacles, as well as Lev-Lok and QuickPort® inserts. Multiple low voltage divider slots accommodate different receptacle sizes

*\*Protective cover included*

*\*Poke-Through covers are sold separately from the PT500 system; All covers come with low voltage divider (except pre-wired versions)*

### Technical Information

#### Environmental Specifications

**Duration Of Fire Protection :** Certified for Fire Resistance in 1, 1-1/2 & 2hr fire rated concrete floors

**Operating Temperature :** -40°C to 70°C

#### Material Specifications

**Feature :** Intumescent Block, Insulation, EMT Pipe, Data & Conduit Connectors

**Mounting Flange :** Aluminium

**Plate Material :** Steel

#### Mechanical Specifications

**Conduit Feeds :** Power Feed 3/4" EMT Conduit, Data Feed 1 1/2" EMT Conduit Connector

**Conduit Selection :** 1 1/2" EMT Conduit for Data

**Cubic Inch Capacity :** 23.7cu. in.

**EMT Pipe Size :** 12"

**Poke-Through Hole :** 5" to 5 1/4" Hole

#### Product Features

**Device Type :** Poke-Through Floor Box System

**Type :** Poke-Through

#### Standards & Certifications

**Applicable Standards :** UL514A, UL263, CSA C22.2 No. 18.1, NOM ANCE

**Certification/Listing :** cULus

**UL File No. :** E92327, R40253

### SPECIFICATION SUBMITTAL

|                      |                      |                      |
|----------------------|----------------------|----------------------|
| JOB NAME:            | CATALOG NUMBERS:     |                      |
| <input type="text"/> | <input type="text"/> | <input type="text"/> |
| JOB NUMBER:          | <input type="text"/> | <input type="text"/> |

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):  
+1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-  
1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

