



Color: Bronze

Weight: 149.9 lbs

Project:

Type:

Prepared By:

Date:

Technical Specifications

Compliance

CSA Listed:

Suitable for wet locations

Construction

Description:

Steel pole 6" taper 11 gauge 20 foot drilled two sides square base

Base Shaft Diameter:

6"

Top Diameter:

3.25"

Hand Holes:

Reinforced with grounding lug and removable cover

Base Plates:

Slotted base plates 36,000 p.s.i.

Color:

Bronze powder coating

Height:

20 FT

Gauge:

11

Wall Thickness:

1/8"

Anchor Bolt Templates:

WARNING Template must be printed on 12" x 18" sheet for actual size. CHECK SCALE BEFORE USING. Templates shipped with anchor bolts and available [online](#).

Max EPA's/Max Weights:

70MPH 17.5 ft./550 lb.
 80MPH 12.6 ft./525 lb.
 90MPH 8.7 ft./500 lb.
 100MPH 6.2 ft./500 lb.
 110MPH 4.4 ft./500 lb.
 120MPH 3.0 ft./500 lb.
 130MPH 1.8 ft./220 lb.
 140MPH 1.0 ft./400 lb.
 150MPH 0.9 ft./390 lb

Accessories:

Base/Cap: BCK-RT6/20

Anchor Bolts: [BOLT5-8](#)

Other

Terms of Sale:

Pole Terms of Sale is available [online](#).


Technical Specifications (continued)

Other

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions



Features

- Designed for ground mounting
- Heavy duty TGIC polyester coating
- Reinforced hand holes with grounding lug and removable cover for easy wiring access
- Pole caps, base covers & bolts are sold separately
- Custom manufactured for each application

Ordering Matrix

Family	Shape	Size	Gauge	Height	Drilled/Welded Tenon
P	TR	6	11	20	D2
R = Round		4 = 4"	7 = 7	10 = 10'	D2 = Drilled
TR = Taped Round		5 = 5"	11 = 11	15 = 15'	WT = Welded Tenon
		6 = 6"		20 = 20'	
		7 = 7"		25 = 25'	
		8 = 8"		30 = 30'	