

WAC LIGHTING

Lotos 4" & 6" Square

Downlight 5CCT

Model	Beam	Color Temp & CRI	Lumens	Finish
R4ESDR R6ESDR	W	9CS 2700K/3000K/3500K/4000K/5000K - 90 9CS 2700K/3000K/3500K/4000K/5000K - 90	600 950	WT White

Example: **R4ESDR-W9CS-WT**

DESCRIPTION

The wafer-thin Lotos LED Recessed Kit with remote driver combines high quality light output and efficiency while eliminating the need for a large housing. This innovative design can be installed easily as a remodel or new construction with an optional frame-in kit sold separately. Lotos is available in a downlight version for general ambient lighting and an adjustable version with a gimbal that pivots 360 degrees on a hinge. Now available with 5-CCT options.

FEATURES

- 5-CCT Switchable between 2700K and 5000K
- Multiple LED array for uniform illumination
- Driver included
- 5 year warranty

SPECIFICATIONS

Construction:	Steel with acrylic diffuser
Power:	8W, 14W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED
Lens:	Translucent acrylic diffuser
Rated Life:	50000 Hours
Mounting:	Heavy gauge retention clips secures fixture to ceiling
Cut Out:	6 1/4", 4 1/4"
Finish:	Electrostatically Powder Coated: White
Ceiling Thickness:	1/2" - 1 1/2"
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8 Compliant, IC, Airtight

Fixture Type:

Catalog Number:

Project:

Location:




FINISHES:



White

LINE DRAWING:



WAC LIGHTING

Lotos 4" & 6" Square Downlight 5CCT

Fixture Type:

Catalog Number:

Project:

Location:

ACCESSORIES

Model	Description	Finish
-------	-------------	--------