



Color: White

Weight: 0.3 lbs

Project:

Type:

Prepared By:

Date:

Driver Info

Type	Constant Current
120V	70
208V	N/A
240V	N/A
277V	N/A
Input Watts	8W

LED Info

Watts	8W
Color Temp	5000K
Color Accuracy	90 CRI
L70 Lifespan	50,000 Hours
Lumens	715
Efficacy	87.5

Technical Specifications

Performance

Product Type:

Retrofit

Lumens (Nominal):

700lm

Efficacy:

87.5 lm/W

Color Accuracy (CRI):

90 CRI

Lifespan:

50,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

Other

LEDs:

LED array provides a uniform source with high efficiency and no pixilation

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Equivalency:

Equivalent to 65W Incandescent

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

LED Characteristics

Color Temperature:

5000K

Electrical

THD:

 $\leq 20\%$

Power Factor:

 ≥ 0.9

Dimmable:

TRIAC and ELV (at 120V only).

Input Voltage:

120V

Technical Specifications (continued)

Electrical

Operating Frequency:

60Hz

Operating Temperature:

-30°C - 40°C

Construction

Size:

4"

Shape:

Round

Housing Material:

Metal

Finish:

White

Trim Style:

Baffle Trim

Lens:

Regressed lens constructed from impact resistant polycarbonate. Convex lens gives the optic a similar lamp-like appearance. Provides smooth and diffuse light distribution.

Gaskets:

Achieve restrictive airflow requirements without additional caulking

Base Type:

E26

Mounting:

Pre-installed friction clips are designed to fit 4" compatible recessed housings

Compliance

Safety Listing:

UL Classified

Environment:

Wet

Fixture Rating:

Enclosed

ENERGY STAR V2.2:

This product is ENERGY STAR® Version 2.2 Certified.

Energy Star ID:

2366455

T20 Compliant:

Yes

Lawful for Sale in California:

Yes

RoHS:

Mercury and UV free. RoHS-compliant components.


FCC:

Complies with Part 15 of the FCC Rules

Model Number:

DLR0109(R4R8950120WB)

Dimensions



Features

- High Performance LEDS up to 100 lm/w
- Use to replace up to 100W traditional light sources
- Durable metal construction: dent and scratch resistant
- UL wet location rated
- Compatible with most standard recessed housings
- Dimmable down to 5% on compatible dimmers
- Available in Round 4" 850lm and 6" 850lm, 1050lm and 1400lm
- Available in 5 color temperatures: 2700K, 3000K, 3500K, 4000K, & 5000K
- Available in a smooth and baffle trim option
- Color designer trims as optional accessories available
- 5-Year, No-Compromise Warranty

Ordering Matrix

Family	Size	Shape	Wattage	CRI/Color Temp	Voltage	Finish	Trim
R	4	R	8	950	120	W	B
	4 = 4"	R = Round	7 = 7W	950 = 90 CRI, 5000K	120 = 120V	W = White	B = Baffle
	6 = 6"	S = Square	8 = 8W	940 = 90 CRI, 4000K			S = Smooth
			10 = 10W	935 = 90 CRI, 3500K			
			11 = 11W	930 = 90 CRI, 3000K			
			14 = 14W	927 = 90 CRI, 2700K			