

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Lotos

Downlight 3000K

Model	Beam	Color Temp & CRI	Lumens	Finish
R4ERDR R6ERDR	W 100°	930 3000K - 90	550 960	WT White

Example: **R4ERDR-W930-WT**

DESCRIPTION

Shallow profile LED that is designed to fit in in furred down ceilings without sacrificing lumen output. Available in 4" or 6" recessed or 4" adjustable LED recessed.

FEATURES

- Multiple LED array for uniform illumination
- Ultra-slim profile
- Driver included
- 5 year warranty

SPECIFICATIONS

Construction:	Steel with translucent acrylic diffuser
Power:	14W, 9W
Input:	120 -277 VAC, 50/60Hz
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED
Lens:	Translucent acrylic diffuser
Rated Life:	50000 Hours
Mounting:	Heavy gauge retention clips secures fixture to ceiling
Cut Out:	6 1/4", 4 1/4"
Finish:	Electrostatically powder coated: White
Ceiling Thickness:	1/2" - 1"
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8-2019 Compliant, IC, Airtight



FINISHES:



White

LINE DRAWING:

