

## S9711

25T5/LED/46-850/DR 25 watt T5 LED; Miniature bi-pin base; 5000K; 50000 average rated hours; 3200 lumens



## Features

- Direct Replacement for use on Electronic Instant Start and Rapid Start ballasts with no rewiring required\*
- Ballast required
- Solid State LED lighting
- High efficacyLong life
- 54watt Fluorescent equivalencyDLC Qualified
- Approved for enclosed luminaires
- 5 year Limited warranty

\*May not be compatible with all instant start ballasts.

View: Ballast Compatibility Chart

S9711

Item N	Number UPC		Watts	Vatts Fluores Equiva			Lamp Shape	Base	Base		La	mp Code
S9 <sup>-</sup>	S9711 045923097119		25	54W			T5	Miniature E	niature Bi Pin		25T5/LED/46-850/DR	
Dimm	Dimmable/Non-Dimmable Finish			L In MOD In hes Inches			Initial Lume	ne i	Average Rated Hours		Kelvin Temp	Color
I	Non-Dimmable	White	4	8''	0.625"		3200	5	50000		5000	Natural Light
CRI	Beam Spread Deg	Operatir	ig Tempe	rature	Pack	Pac	ckage Type	DLC IE	):	RoHS	Compliant	UL or ETL Listed
82	185	-20°C (-4°F) to a maximum of +45°C (113°F)			10		Вох	PRVRXZXF DLC Search			Yes	Yes
UL Classification Wa											Warranty	
	cULus Classified - Damp Location Rated 5 Year Limited											



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051