



S9927

12T8/LED/36-835/BP

12 watt T8 LED; Medium bi-pin base; 3500K; 50000 average rated hours; 1400 lumens

Features

- All glass tube
- Direct wire 120-277V line voltage*
- Double ended wiring
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S9927

*Existing wiring to both sockets can remain in place

*Will work on both shunted or non-shunted sockets

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Lamp Shape	Base
S9927	045923099274	120-277	12	50/60Hz	25W	T8	Medium Bi-Pin

ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
G13	12T8/LED/36-835/BP	Non-Dimmable	White	36"	1.00"	1400	50000

Kelvin Temp	Color	CRI	Beam Spread Deg	Pack	Package Type	CEC Status	RoHS Compliant
3500	Neutral White	82	220	10	Box	Lawful for sale in California	Yes

UL or ETL Listed	UL Classification	Warranty
Yes	cULus - Damp Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051