

SLC12L125PTC



SLC12L125PTC, 1Ø, 12 Ckt, 125 A, MLO

General Information

Extended Product Type	SLC12L125PTC
Product ID	2CRT121243Z1113
EAN	888614629271
Catalog Description	SLC12L125PTC, 1Ø, 12 Ckt, 125 A, MLO
Long Description	SETRICITY™ 12 circuit, 125 A Main Lug Load Center for 120/240 V single phase electrical systems in a NEMA 1 indoor rated enclosure, with a grey powder coated cover and galvanized steel enclosure

Ordering

EAN	888614629271
Minimum Order Quantity	1 piece
Customs Tariff Number	8537109050

Dimensions

Product Net Width	362 mm 14.25 in
Product Net Height	496 mm 19.5 in
Product Net Depth / Length	100 mm 3.94 in
Product Net Weight	7.5 kg 16.5 lb

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	407 mm 16 in
Package Level 1 Height	134 mm 5.25 in
Package Level 1 Depth / Length	534 mm 21 in
Package Level 1 Gross Weight	7.8 kg 17 lb
Package Level 1 EAN	888614629271

Environmental

RoHS Status	No declaration needed
-------------	-----------------------

Additional Information

Cover Color	Grey
Housing Material	Galvanized Steel
Product Main Type	SENTRICITY™
Product Name	Indoor Load Center, MLO
Rated Current (I _n)	125 A
Rated Operational Voltage	120/240 V AC
Standards	UL 67 QEUY:E319800

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	9AKK106930A6925
Declaration of Conformity - CE	No Certification needed
Instructions and Manuals	9AKK107045A3372
UL Certificate	9AKK107045A4503

Classifications

ETIM 5	EC002274 - Busbar housing
ETIM 6	EC002274 - Busbar housing
UNSPSC	39121101
WEEE Category	Product Not in WEEE Scope

Categories

Low Voltage Products and Systems → Load Centers → Residential Load Centers & Components → Load Centers