
Self-Regulating Pipe Trace Cable





Model Code:

SR 12 3 -250 A B C D

A: Self Regulating Cable

B: 12 - 120V

24 - 240V

C: Watts per foot

D: Linear Length in feet

SR Series Self-Regulating Heating Cable is designed for a variety of industrial and commercial pipe trace applications.

SR Self-Regulating Heating Cable Features

- Stops pipe and valve freeze down to -40°F
- Cable will not overheat or burn out when overlapped
- Suitable for use on metal and plastic pipes
- 2 year warranty



| | | | | AVAILABLE LENGTHS | | |
|--------------|-------|-------------------------|-------------------------------|-------------------------------|--------------------------------|----------------|
| | VOLTS | PIPE RATING** WATTS/FT. | 100 FT. LENGTH MODEL / UPC | 250 FT. LENGTH Model / UPC | 1000 FT. LENGTH MODEL / UPC | WEIGHT/FT. |
| 120V 240V | 120 | 3 | SR123-100 / 40513 | SR123-250 / 40414 | SR123-1000 / 40416 | 0.080 LBS./FT. |
| | 120 | 5 | SR125-100 / 40514 | SR125-250 / 40418 | SR125-1000 / 40420 | 0.080 LBS./FT. |
| | 120 | 8 | SR128-100 / 40515 | SR128-250 / 40422 | SR128-1000 / 40424 | 0.080 LBS./FT. |
| | 120 | 10 | SR1210-100 / 40516 | SR1210-250 / 40426 | SR1210-1000 / 40428 | 0.080 LBS./FT. |
| | VOLTS | PIPE RATING** WATTS/FT. | 100 FT. LENGTH Model / UPC | 250 FT. LENGTH Model / UPC | 1000 FT. LENGTH MODEL / UPC | WEIGHT/FT. |
| | 240* | 3 | SR243-100 / 40517 | SR243-250 / 40430 | SR243-1000 / 40432 | 0.080 LBS./FT. |
| | 240* | 5 | SR245-100 / 40518 | SR245-250 / 40434 | SR245-1000 / 40436 | 0.080 LBS./FT. |
| | 240* | 8 | SR248-100 / 40519 | SR248-250 / 40438 | SR248-1000 / 40440 | 0.080 LBS./FT. |
| | 240* | 10 | SR2410-100 / 40520 | SR2410-250 / 40442 | SR2410-1000 / 40444 | 0.080 LBS./FT. |
| | | PIPE RATING** | | CUT TO LENGTH | | |
| 120V | VOLTS | WATTS/FT. | | MODEL / UPC | | WEIGHT/FT. |
| | 120 | 3 | | SR123 / 40446 | | 0.080 LBS./FT. |
| | 120 | 5 | | SR125 / 40450 | | 0.080 LBS./FT. |
| | 120 | 8 | | SR128 / 40454 | | 0.080 LBS./FT. |
| | 120 | 10 | | SR1210 / 40458 | | 0.080 LBS./FT. |
| | | PIPE RATING** | | CUT TO LENGTH | | |
| | VOLTS | WATTS/FT. | | MODEL / UPC | | WEIGHT/FT. |
| 240V | 240* | 3 | | SR243 / 40448 | | 0.080 LBS./FT. |
| | 240* | 5 | | SR245 / 40452 | | 0.080 LBS./FT. |
| | 240* | 8 | | SR248 / 40456 | | 0.080 LBS./FT. |
| | 240* | 10 | | SR2410 / 40460 | | 0.080 LBS./FT. |

^{**}Wattage rating for pipe freeze protection application is determined at 40°F (5°C).

Controls and thermostats should always be used with King heating cable systems.

SR ACCESSORIES Refer to page 36 for SR Accessories

| MODEL | UPC | DESCRIPTION | WEIGHT |
|-------|-------|-----------------------------------------------------------------|----------|
| SRK00 | 40462 | Hard wired power connection kit, includes end seal | 0.3 lbs. |
| SRK02 | 40461 | Connection kit, includes end seal | 0.3 lbs. |
| SRK03 | 40464 | Pipe trace tape (66 ft) and labels | 0.1 lbs. |
| SRK08 | 40466 | Plug in 120V connection kit with GFEP device, includes end seal | 1.0 lbs. |
| SRK10 | 40468 | Weatherproof splice/tee kit, includes end seal | 0.2 lbs. |
| SRK12 | 40470 | End seal kit (2 per package) | 0.1 lbs. |
| SRK14 | 40473 | 3M VHB double sided acrylic foam pads (25 per package) | 0.1 lbs. |
| SRK15 | 40476 | Downspout hanger and cable ties | 0.3 lbs. |
| SRK17 | 40477 | 11 & 13mm Gel end seal | 0.1 lbs. |

^{*}Approved for 208, 220, 240, 277 volt operation, refer to wattage adjustment tables for output rating (Table 4 Page 28).