


# InvisiLED® CCT

## Color Temperature Adjustable Tape

# WAC LIGHTING



Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

Architectural grade white tape light that delivers precise color consistency and brightness throughout the strip. 5 CCTs selectable and best-in-lighting quality make it perfect for applications like bright coves or task lighting in dry or damp locations.

### FEATURES

- May be cut and easily reconnected every 4 inches
- Select and choose desirable CCT with matching CCT selectable power supply
- InvisiCoat, a UV stabilized protective coating, protects LEDs and circuitry for long term use in Damp Locations
- Equal brightness for an entire light strip
- Strong adhesive bonding with the 3M adhesive VHB
- Gold plated connector protects from corrosion, heat, and ensures a reliable connection
- 100 ft max distance between the power supply and beginning of InvisiLED®
- Closet Rated options (T24-CS1 & T24-CS2)

### SPECIFICATIONS

<b>Construction:</b>	Flexible strip light
<b>Cutting Interval:</b>	4"
<b>Input:</b>	24VDC
<b>Lumens:</b>	Up to 600 lm/ft
<b>Max Run:</b>	Refer to ordering table
<b>Dimming:</b>	ELV, 0-10V
<b>CRI:</b>	95+
<b>McAdams Steps:</b>	2
<b>Color Temp:</b>	2700K / 3000K / 3500K / 4000K / 5000K
<b>Rated Life</b>	50,000 hours
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	UL & cUL listed, Damp Location listed, Title 24 Compliant

### TAPE SELECTIONS

System	Max Run	Power	Length (in feet)					Color Temp		Finish
<b>T24-CS1</b>	100+lm/ft	60 ft	1.2W/ft	<b>01</b>	<b>05</b>	<b>10</b>	<b>20</b>	<b>60</b>	2700K	<b>WT White</b>
<b>T24-CS2</b>	200+lm/ft	40ft	2.4W/ft	<b>01</b>	<b>05</b>	<b>10</b>	<b>20</b>	<b>40</b>	3000K	
<b>T24-CS3</b>	300+lm/ft	30ft	3.0W/ft	<b>01</b>	<b>05</b>	<b>10</b>	<b>20</b>	<b>30</b>	3500K	
<b>T24-CS4</b>	400+lm/ft	20ft	4.6W/ft	<b>01</b>	<b>05</b>	<b>10</b>	<b>20</b>	N/A	4000K	
<b>T24-CS6</b>	600+lm/ft	15ft	6.3W/ft	<b>01</b>	<b>05</b>	<b>10</b>	<b>15</b>	N/A	5000K	











Example: **T24-CS3-10-2750WT**

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585


Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

	Model	Finish	
	<b>T24-MM-WT</b>	White	Tape to Tape Connector Connects tape sections
	<b>T24-TI-WT</b>	White	Tape to Tape T Connector Connects tape sections
	<b>T24-XI-WT</b>	White	Tape to Tape X Connector- Connects tape sections
	<b>T24-LI-WT</b>	White	Tape to Tape L Connector Connects tape sections
	<b>T24-FF-WT</b>	White	Joiner Cable Extender Connects joiner cable to joiner cable, female on both sides
	<b>T24-Y-WT</b> <b>T24-Y-BK</b>	White Black	Flex Tape to Tape Y Connector Connects tape sections
	<b>T24-CT-CL1</b>	Clear	Plastic Mounting Clip For installation on non-flat surfaces (10 pcs/ pack)
	<b>T24-X-WT</b> <b>T24-X-BK</b>	White Black	Flex Tape to Tape X Connector Connects tape sections
	<b>T24-IC-002</b> <b>T24-IC-006</b> <b>T24-IC-012</b> <b>T24-IC-036</b> <b>T24-IC-072</b> <b>T24-IC-144</b> <b>T24-IC-240</b>	<b>WT</b> White <b>BK</b> Black	In Wall Rated Joiner Cable Connects tape sections, 2 male ends
	<b>T24-EX3-072</b> <b>T24-EX3-144</b> <b>T24-EX3-240</b> <b>T24-EX3-1200</b>	<b>WT</b> White <b>BK</b> Black	In Wall Rated Extension Cable Extends distance between a hard wire power supply or a wiring box to a tape section
			2 in 6 in 1 ft 3 ft 6 ft 12 ft 20 ft
			Example: <b>T24-IC-002-WT</b>
			6 ft 12 ft 20 ft 100 ft
			Example: <b>T24-EX3-072-WT</b>

## Power Supply

	Model	Input	Output	Dimming	
	<b>PS-24DC-U60R-CS-SM</b> <b>PS-24DC-U96R-CS-SM</b>	<b>120V-277VAC</b>	24VDC 60W 24VDC 96W	ELV / 0-10V	7 11/16" x 3 7/8" x 1 3/8" ≥ 0.9 pf Overload and short circuit protection Includes 6ft lead wire with connector