

InvisiLED® OUTDOOR

Wet Rated LED Tape

WAC LIGHTING



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Designed for the outdoors, this durable and professional grade white tape light delivers superior color consistency and brightness throughout the strip. An IP65 Outdoor Wet Location rating, and unique silicon tube protection guards against the elements while offering 3 CCT choices to illuminate hardscaping, landscaping and architectural features.

FEATURES

- May be cut every 4 inches
- Beam Spread: 115°
- Multiple roll lengths offered
- Equal brightness from end to end
- Protection against water spray, dust with silicone jacket (IP65)
- 100 ft max distance between the power supply and beginning of InvisiLED®

SPECIFICATIONS

Construction:	Flexible strip light in silicon tube
Cutting Interval:	4"
Input:	24VDC
Lumens:	Up to 200 lm/ft
Max Run:	Refer to ordering table
Dimming:	ELV, TRIAC
CRI:	90
McAdams Steps:	3
Color Temp:	2700K / 3000K/ 4000K
Rated Life	50,000 hours
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL & cUL listed, Wet Location listed, Title 24 Compliant

TAPE SELECTIONS

System	Max Run		Power	Length (in feet)						Color Temp		Finish
T24-OD1	100+lm/ft	80ft	1.2W/ft	01	05	10	20	40	80	27	2700K	Black
T24-OD2	200+lm/ft	40ft	2.4W/ft	01	05	10	20	40	N/A	30	3000K	
										40	4000K	

Example: **T24-OD1-20-27**

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

	Model	Finish		
	T24-WE-IC-002-BK T24-WE-IC-006-BK T24-WE-IC-012-BK T24-WE-IC-036-BK T24-WE-IC-072-BK T24-WE-IC-144-BK T24-WE-IC-240-BK	<i>Black</i>	<i>2 in</i> <i>6 in</i> <i>1 ft</i> <i>3 ft</i> <i>6 ft</i> <i>12 ft</i> <i>20 ft</i>	InvisiLED Outdoor Joiner Cable <i>Extends power supply lead wire</i>
	T24-WE-BO12-BK T24-WE-BO72-BK	<i>Black</i>	<i>1 ft</i> <i>6 ft</i>	InvisiLED Outdoor Lead Wire <i>Connects to Indoor Power Supply</i>
	T24-WE-EX2-006-BK	<i>Black</i>	<i>6 in</i>	InvisiLED Outdoor Power Connector Kit with Wire Jacket and Silicone Sealant <i>Allows power to Wet Rated tape</i>
	T24-WE-Y-BK	<i>Black</i>		InvisiLED Outdoor Tape to Tape Y Connector <i>Splits power to the two tape sections</i>
	T24-WE-EC	<i>Clear</i>		Wet Rated Tape End Cap with Silicone Sealant <i>24VDC Wet Rated (10 pieces)</i>
	LED-TO24-C1	<i>Black</i>		InvisiLED Outdoor Surface Mounting Clip <i>24VDC Wet Rated Mounting Screws (10 pieces)</i>
	LED-TO24-C2	<i>Black</i>		InvisiLED Outdoor Edge Mounting Clip <i>24VDC Wet Rated Tape Mounting Screws (10 pieces)</i>
	T24-WE-C3	<i>Black</i>		InvisiLED Outdoor Underside Mounting Clip <i>24VDC Wet Rated Tape Mounting Screws (10 pieces)</i>
	T24-WE-CH5	<i>Clear</i>	<i>5ft</i>	InvisiLED Outdoor Surface Mount Clear Channel
	T24-WE-SI-45	<i>White</i>		Silicone Sealant <i>Wet Location Tape Sealant (45 grams)</i>

Power Supply

	Model	Input	Output	Dimming	
	PS-24DC-U96R-WE	120V-277VAC	<i>24VDC 96W</i>	<i>ELV / TRIAC</i>	<i>8 3/8" x 2 13/16" x 1 11/16"</i> <i>≥ 0.9 pf</i> <i>Overload and short circuit protection</i> <i>Includes 6ft lead wire</i>
	PS-24DC-A96P-WE	120V	<i>24V 96W</i>	<i>N/A</i>	<i>8 3/8" x 2 13/16" x 1 11/16"</i> <i>≥ 0.9 pf</i> <i>Overload and short circuit protection</i> <i>Includes 6ft lead wire</i> <i>120V input power cord ready</i>