



UPC Code: 07847776243

Country Of Origin: Mexico

NEMA:
5-20R



TDR20-S2G

20 Amp, 125 Volt, NEMA 5-20R, 2P, 3W, Spec Grade, Decora Receptacle, 2 Plug Controlled Markings, Straight Blade, Self Grounding, Back & Side Wired - GRAY

Leviton offers custom imprinting solutions to meet the 2014 National Electrical Code requirements for identifying receptacles that will be automatically de-energized as part of an overall plug load control program. All 15A & 20A, 125V receptacles that are automatically controlled will be marked with a specific symbol.

Technical Information

AC Horsepower Ratings

At Rated Voltage: 1/2 HP

Electrical Specifications

Amperage: 20 A

Voltage: 125 VAC

Grounding: Self-Grounding

Pole: 2

Wire: 3

Dielectric Voltage: Withstands 2000V per UL498

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Environmental Specifications

Flammability: Rated V-2 per UL94

Operating Temperature: -40°C to 60°C

Material Specifications

Face Material: Polypropylene

Body Material: Nylon

Line Contacts: Brass Triple Wipe .031 Thick

Terminal Clamp: Plated Steel

Terminal Screws: Plated Steel

Grounding Screw: Plated Steel

Strap Material: Zinc-Plated Steel 0.042

Ground Clips: Brass

Mechanical Specifications

Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Terminal Accom.: 14-10 AWG

Wire Type: Solid or Stranded Building Wire

Product ID: Ratings are permanently marked on device

Termination: Back or Side Wire

Product Features

Color: Gray

NEMA: 5-20R

Device Type: Duplex Receptacle Outlet

Feature: Two Outlets Marked Controlled

Feature 2: Tamper-Resistant

Feature 4: Smooth Face

Grade: Heavy-Duty Industrial Specification Grade

Brand: Decora Plus

Standards and Certifications

NEMA: WD-1 & WD-6

ANSI: C-73

Certification/Listing: UL, CSA, NOM-ANCE

Applicable Standards: UL 498, CSA C22.2 No. 42

Warranty

Warranty: 10-Year Limited

Patents*

CA2483480

US6743029

CA2621644

US7355117

CA2624409

US7820909

CA2677283

US7868719

CN200880004760.2


US8242362

MX257790

US8684771

MX321216

*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.



SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/> JOB NUMBER: <input type="text"/>	CATALOG NUMBERS: <input type="text"/> <input type="text"/> <input type="text"/> <input type="text"/>
-------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):
+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-
1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

