

Project:	Туре:
Prepared By:	Date:

Driver Info		LED Info	
Type: 120V: 208V: 240V: 277V: Input Watts: Efficiency:	Constant Current 1.53A N/A N/A N/A 130W 93%	Watts: Color Temp: Color Accuracy: L70 Lifespan: Lumens: Efficacy:	120W 5000K (Cool) 75 CRI 18,000 14,012 108 LPW
Emoicrity.	3370		

Technical Specifications

Listings

UL Listing:

Suitable for wet locations

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80

Electrical

THD:

5.4% at 120V

Power Factor:

99.8% at 120V

Driver:

Constant Current, 120V: 1.53A

Surge Protection:

2kV

LED Characteristics

LEDs:

Long-life, high-efficacy surface mount LEDs

Lifespan:

18,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

Color Stability:

LED color temperature is warrantied to shift no more than 200K in CCT over a 5 year period

Color Uniformity:

RAB's range of CCT (Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Construction

IP Rating:

Ingress Protection rating of IP65 for dust and water

Ambient Temperature:

-20°C to 40°C

Housing:

Aluminum

Thermal Management:

Superior thermal management with external Air-Flow fins

Lens:

Polycarbonate lens

Mounting:

Clip on carabiner

Gasket:

High temperature silicone

Green Technology:

Mercury and UV-free. RoHS compliant components.

Finish:

Formulated for high-durability and long lasting color

Other

2 Yr Limited Warranty:

The RAB 2-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at

Equivalency:

Replaces 320W Metal Halide

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Features

Portable solution for job sites

Impact resistant and protected against dust and water

Daisy chain capability

Carabiner hook for easy mounting

TEMPLED120G/120/10CP



Ordering Matrix					
Family	Wattage	Wire Guard	Voltage		
TEMPLED	120	G	/120/10CP		
	100 = 86W 120 = 130W	G = Wire Guard	/120/10CP = 120V w/ 10ft Cord & Plug		