


Tamper resistant receptacles

Single and duplex receptacles

Product description

2-pole, 3-wire grounding
15A, 125V/AC; 20A, 125V/AC



5-15R


5-20R

Design features

- Tamper resistant receptacles provide compliance with 2014 NEC® Article 406.12 which states that all 15A and 20A, 125V/AC receptacles installed in dwelling units must be tamper resistant
- "TR" designation provides visual identification
- High impact-resistant thermoplastic face and back body eliminates breakage
- Patented built-in wire stripper for #14 and #12 AWG wire to speed installation
- Push-in terminals accept #14 AWG solid wire for quick installation
- Double-wire ground contacts ensure long-term ground retention
- Side wire terminals accept up to #10 AWG solid wire




Residential grade tamper resistant receptacles



Rating	A	V/AC	NEMA	Description	Color suffix	Catalog no.		
15	125	5-15R		Tamper resistant duplex receptacle, side & push wire	A, B, BK, LA, V, W	□ TR270__	•	•
				Auto grounding tamper resistant duplex receptacle, side & push wire	A, B, LA, V, W	□ TR270-9__	•	•
				Tamper resistant single receptacle, with clock hanger, side wire	W	□ TR775__	•	•
				Tamper resistant decorator duplex receptacle, side & push wire	A, B, BK, GY, LA, V, W	□ TR1107__	•	•
				Auto grounding tamper resistant decorator duplex receptacle, side & push wire	A, B, BK, LA, V, W	□ TR1107-9__	•	•
15	125			Aspire duplex receptacle	DS, SG, WS	□ 9505TR__		
				Aspire single receptacle	DS, SG, WS	□ 9507TR__		
20	125	5-20R		Tamper resistant duplex receptacle, side wire	A, B, BK, GY, LA, V, W	□ TR370__	•	
				Aspire single receptacle, side & back wire	AW, DS, SG, WS	□ 9508TR__		
				Aspire duplex receptacle, side & back wire	AW, DS, SG, WS	□ 9510TR__		

cULus Listed to UL498, file no. E15058; NOM certified

Commercial grade tamper resistant receptacles



Rating	A	V/AC	NEMA	Description	Color suffix	Catalog no.		
15	125	5-15R		Single receptacle, side wire	A, B, BK, LA, V, W	□ TR817__*	•	•
				Duplex receptacle, back & side wire	A, B, BK, GY, LA, V, W	□ TRBR15__	•	•
				Duplex receptacle, back & side wire	A, B, BK, GY, LA, V, W	□ TR5262__	•	•
				Decorator single receptacle, back & side wire	B, BK, V, W	□ TR6250__	•	•
				Decorator duplex receptacle, back & side wire	LA, V, W	□ TR6252__	•	•
20	125	5-20R		Single receptacle, side wire	A, B, BK, LA, V, W	□ TR1877__*	•	•
				Duplex receptacle, back & side wire	A, B, BK, GY, LA, RD, V, W	□ TRBR20__	•	•
				Duplex receptacle, back & side wire	A, B, BK, GY, LA, RD, V, W	□ TR5362__	•	•
				Decorator single receptacle, side wire	LA, V, W	□ TR6350__	•	•
				Decorator duplex receptacle, back & side wire	A, B, BK, GY, LA, V, W	□ TR6352__	•	•

* Not Fed Spec

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), GY (Gray), LA (Light Almond), RD (Red), V (Ivory), W (White), AW (Alpine White), DS (Desert Sand), SG (Silver Granite), WS (White Satin)

A	B	BK	GY	LA	RD	V	W
(Almond)	(Brown)	(Black)	(Gray)	(Lt. Almond)	(Red)	(Ivory)	(White)
AW	AW	DS	DS	SG	SG	WS	WS
(Alpine White)		(Desert Sand)		(Silver Granite)		(White Satin)	

ArrowLink option available. Add "MOD" suffix to standard catalog number (example TR5262WMOD).
For ordering information on ArrowLink SPD connectors, see ArrowHart Buyers Guide

Indicates NAFTA compliant RoHS compliant Tamper resistant Build-to-spec customizable devices

Specification information: Page 8

Compliances, specifications and availability are subject to change without notice.



TR270



TR1107



TR6352